

BLAIR TOP RGB

BLAIRT0380024DC14467RGB000C03
Article no.: 101390

BETTER LIGHT





IP67	50.0 mm	RGB K	380 lm
Degree of protection (IP)	Length of particular segments	Colour temperature	Luminous flux per meter

TENDER TEXT

BILTONAIR TOP 380 LED strip 24VDC 14,4W/m IP67 RGB COLOR 3m LED module BLAIR TOP RGB Article 101390 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 36000 h . The BLAIR TOP RGB LED-strip has a luminous flux of 380 lm at 14.4 W, resulting in an efficiency of 36 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 3000 mm can be achieved. In terms of lighting, the module has a colour temperature of RGB and a beam angle of 120°. All this with a colour rendering index of ohne and a Binning selection based on (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 8.3 mm. Degree of protection IP67 Dimension (L x W x H): 3020.0 mm x 13.2 mm x 12.0 mm

TOP-FEATURES

//__ IP67 protection in highly flexible silicone jacket

//__ Unlimited design flexibility in shape and color

//__ Effective light scenarios with a strong colour spectrum

//__ Wave-shaped bendable in direction of the light-emitting surface

24 V | RGB | IP67 | RoHS COMPLIANT 2002/95/EC | CE

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261124 | Errors and printing errors are reserved.

BLAIR TOP RGB

BLAIRT0380024DC14467RGB000C03
Article no.: 101390

BETTER LIGHT

MECHANICAL DATA

Width [mm]	13.2
Length [mm]	3020.0
Height/depth [mm]	12
Height [mm]	12.0
Colour	RGB
Model	Schlauch
Self-adhesive	nein
Lamp type	LED nicht austauschbar
Distance [mm]	8.3
Distance relating to	LED zu LED
Degree of protection (IP)	IP67
Length of particular segments [mm]	50.0
Lowest bending radius [mm]	200
With connection set	Yes
With end piece	Yes
Number of lamps per meter	120

ELECTRICAL DATA

Protection class	ohne
Voltage type	DC
Lamp voltage [V]	24
Lamp power per meter [W]	14.4
Overall efficiency [lm/W]	36

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	ohne
Colour temperature [K]	RGB
Colour of light	RGB
Luminous flux per meter [lm]	380

CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	4
Max. length [mm]	3000

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	- 20 ... + 50
Ambient temperature during operating [°C]	- 20 ... + 45
Rated life time L70/B10 at 25 °C [h]	36000

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261124 | Errors and printing errors are reserved.

BLAIR TOP RGB

BLAIRT0380024DC14467RGB000C03
Article no.: 101390

PACKAGING INFORMATION

EAN	4250716933703
Article no.	101390
Gross width [mm]	330.0
Gross height [mm]	27.0
Gross length [mm]	330.0
Customs tariff number	94054039
Net width [mm]	13.2
Net height [mm]	12
Net length [mm]	3020
State of origin	AT

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article	Article no.
Profile AIR TOP	**170885**
Safety clip AIR TOP	**170919**

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261124 | Errors and printing errors are reserved.