


BLECP 1300

BLECP1300024DC12020830000W05

Article no.: 171001



24
V

Lamp voltage

11500
mm

Max. length

>80

Colour rendering index CRI

1240
lm

Luminous flux per meter

TENDER TEXT

BL ECO+ 1300 LED strip 24VDC 12W/m IP20 CRI>80 3000K WHITE 5m LED module BLECP 1300 Article 171001 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BLECP 1300 LED-strip has a luminous flux of 1240 lm at 12.0 W, resulting in an efficiency of 103 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 11500 mm can be achieved. In terms of lighting, the module has a colour temperature of 3000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 8.3 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.2 mm

TOP-FEATURES

- //__ Long line lengths and better stability due to double layer
- //__ Guaranteed LED properties with guaranteed patent protection
- //__ Current regulation via transistors
- //__ To create a homogeneous light image, the band is populated with ###attribute.6040### LEDs per meter

24 V

>80

IP20

3000 K

BLECP 1300

BLECP1300024DC12020830000W05

Article no.: 171001



MECHANICAL DATA

Width [mm]	8.0
Length [mm]	5000.0
Height/depth [mm]	1.6
Height [mm]	1.2
Colour	White
Model	Band
Self-adhesive	yes
Lamp type	LED nicht austauschbar
Distance [mm]	8.3
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments [mm]	50.0
Lowest bending radius [mm]	20
With connection set	yes
With end piece	nein
Number of lamps per meter	120

ELECTRICAL DATA

Protection class	ohne
Voltage type	DC
Lamp voltage [V]	24
Lamp power per meter [W]	12.0
Overall efficiency [lm/W]	103

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Colour temperature [K]	3000
Colour of light	White
Luminous flux per meter [lm]	1240
Energy efficiency class provided exchangeable built-in lamp	F
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	2
Max. length [mm]	11500

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	- 5 ... + 55
----------------------------------	--------------

BLECP 1300

BLECP1300024DC12020830000W05

Article no.: 171001



Operation temperature at Tc [°C]	- 5 ... + 60
Ambient temperature during operating [°C]	- 20 ... + 45
Rated life time L80/B50 at 25 °C [h]	60000

PACKAGING INFORMATION

EAN	4250716936247
Article no.	171001
Net weight [g]	9.8
Gross weight [g]	35
Gross width [mm]	200.0
Gross height [mm]	18.0
Gross length [mm]	200.0
Customs tariff number	94054239
Net width [mm]	8.0
Net height [mm]	1.6
Net length [mm]	1000
State of origin	CN

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of +/- 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at