
BLONE 900 >80

BLO190900024DC06920865000W20

Article no.: 101021










Lamp voltage



Max. length



Colour rendering index CRI Luminous flux per meter



TENDER TEXT

BL ONE 900 LED strip 24VDC 6,9W/m IP20 CRI>80 6500K WHITE 20m LED module BLONE 900 >80 Article 101021 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 $^{\circ}$ C at a service life of 60000 h . The BLONE 900 >80 LED-strip has a luminous flux of 850 lm at 6.9 W, resulting in an efficiency of 123 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 12500 mm can be achieved. In terms of lighting, the module has a colour temperature of 6500 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP20 Dimension (L x W x H): 20000.0 mm x 8.0 mm x 1.5 mm

TOP-FEATURES

// Improvement of homogeneity by 20 additional LEDs per meter

//__ Wide choice of light colors and lumen packages

//_ Wide range of applications for linear lighting in

//__ With a maximum module length of up to 12500 mm long, linear lighting lines can be implemented

//__ UL certification available







BLONE 900 >80

BLO190900024DC06920865000W20

Article no.: 101021



MECHANICAL DATA

| 8.0 |
|------------------------|
| 20000.0 |
| 1.5 |
| 1.5 |
| White |
| Band |
| yes |
| LED nicht austauschbar |
| 7.14 |
| LED zu LED |
| IP20 |
| 50.0 |
| 20 |
| yes |
| nein |
| 140 |
| |

ELECTRICAL DATA

| Protection class | III |
|---------------------------|---------|
| Voltage type | DC |
| Lamp voltage [V] | 24 |
| Imput voltage range [V] | 23 - 25 |
| Lamp power per meter [W] | 6.9 |
| Overall efficiency [lm/W] | 123 |

LIGHT TECHNICAL DATA

| Beam angle [°] | 120 |
|---|-------|
| Colour rendering index CRI | >80 |
| Colour temperature [K] | 6500 |
| Colour of light | White |
| Luminous flux per meter [lm] | 850 |
| Energy efficiency class provided exchangeable built-in lamp | E |
| Colour consistency (McAdam ellipse) | SDCM3 |
| | |

CONNECTION

| Conductor cross section [mm²] | 0.5 |
|-------------------------------|-------|
| Number of poles | 2 |
| Max. length [mm] | 12500 |

TEMPERATURE TECHNICAL DATA

BLONE 900 >80

BLO190900024DC06920865000W20

Article no.: 101021



| Ambient/storage temperature [°C] | - 5 + 55 |
|---|-----------|
| Operation temperature at Tc [°C] | - 5 + 60 |
| Ambient temperature during operating [°C] | - 20 + 45 |
| Rated life time L80/B10 at 25 °C [h] | 60000 |

PACKAGING INFORMATION

| EAN | 4250716933864 |
|-----------------------|---------------|
| Article no. | 101021 |
| Net weight [g] | 199 |
| Gross weight [g] | 319 |
| Gross width [mm] | 200.0 |
| Gross height [mm] | 18.0 |
| Gross length [mm] | 200.0 |
| Customs tariff number | 94054099 |
| Net width [mm] | 8.0 |
| Net height [mm] | 1.5 |
| Net length [mm] | 20000 |
| State of origin | AT |

^{*} Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at