BLONE 2000 >80

BLO192000024DC15320822000W05

Article no.: 101114










Lamp voltage



Max. length



Colour rendering index CRI Luminous flux per meter

1580 lm

TENDER TEXT

BL ONE 2000 LED strip 24VDC 15,3W/m IP20 CRI>80 2200K WHITE 5m LED module BLONE 2000 >80 Article 101114 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 $^{\circ}$ C at a service life of 60000 h . The BLONE 2000 >80 LED-strip has a luminous flux of 1580 lm at 15.3 W, resulting in an efficiency of 103 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 7000 mm can be achieved. In terms of lighting, the module has a colour temperature of 2200 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

TOP-FEATURES

// Improvement of homogeneity by 20 additional LEDs per meter

//__ Wide choice of light colors and lumen packages

//__ Wide range of applications for linear lighting in

//__ With a maximum module length of up to 7000 mm long, linear lighting lines can be implemented

//__ UL certification available















BLONE 2000 >80

BLO192000024DC15320822000W05

Article no.: 101114



MECHANICAL DATA

Width [mm] 8.	.0
Length [mm] 50	000.0
Height/depth [mm] 1.	.5
Height [mm] 1.	.5
Colour	/hite
Model Ba	and
Self-adhesive ye	es
Lamp type LE	ED nicht austauschbar
Distance [mm] 7.	14
Distance relating to	ED zu LED
Degree of protection (IP)	220
Length of particular segments [mm] 50	0.0
Lowest bending radius [mm] 20	0
With connection set ye	es
With end piece ne	ein
Number of lamps per meter 14	40

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Lamp power per meter [W]	15.3
Overall efficiency [lm/W]	103

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Colour temperature [K]	2200
Colour of light	White
Luminous flux per meter [lm]	1580
Energy efficiency class provided exchangeable built-in lamp	F
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	2
Max. length [mm]	7000

TEMPERATURE TECHNICAL DATA

BLONE 2000 >80

BLO192000024DC15320822000W05

Article no.: 101114



Ambient/storage temperature [°C]	- 5 + 55
Operation temperature at Tc [°C]	- 5 + 60
Ambient temperature during operating [°C]	- 20 + 45
Rated life time L80/B10 at 25 °C [h]	60000

PACKAGING INFORMATION

EAN	4250716934175
Article no.	101114
Net weight [g]	49
Gross weight [g]	175
Gross width [mm]	200.0
Gross height [mm]	18.0
Gross length [mm]	200.0
Customs tariff number	94054099
Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	5000
State of origin	AT

^{*} Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at