
BLOPL 1300 >80

BLOPL1300024DC08020840000W05
Article no.: 101972

BETTER LIGHT





24 V	8000 mm	>80	1300 lm
Lamp voltage	Max. length	Colour rendering index CRI	Luminous flux per meter

TENDER TEXT

BL ONE+ 1300 LED strip 24VDC 8W/m IP20 CRI>80 4000K WHITE 5m LED module BLOPL 1300 >80 Article 101972 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BLOPL 1300 >80 LED-strip has a luminous flux of 1300 lm at 8.0 W, resulting in an efficiency of 163 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 8000 mm can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 6.25 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

TOP-FEATURES

//__ Improvement of homogeneity by 20 additional LEDs per meter

//__ Wide choice of light colors and lumen packages

//__ Wide range of applications for linear lighting in white

//__ With a maximum module length of up to 8000 mm long, linear lighting lines can be implemented

24 V | >80 | IP20 | 4000 K | RoHS COMPLIANT 2002/95/EC | CE

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261101 | Errors and printing errors are reserved.

BLOPL 1300 >80

BLOPL1300024DC08020840000W05
Article no.: 101972

BETTER LIGHT

MECHANICAL DATA

Width [mm]	8.0
Length [mm]	5000.0
Height/depth [mm]	1.5
Height [mm]	1.5
Colour	White
Model	Band
Self-adhesive	Yes
Lamp type	LED nicht austauschbar
Distance [mm]	6.25
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments [mm]	50.0
Lowest bending radius [mm]	20
With connection set	Yes
With end piece	nein
Number of lamps per meter	160

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Lamp power per meter [W]	8.0
Overall efficiency [lm/W]	163

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Colour temperature [K]	4000
Colour of light	White
Luminous flux per meter [lm]	1300
Energy efficiency class provided exchangeable built-in lamp	D
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	2
Max. length [mm]	8000

TEMPERATURE TECHNICAL DATA

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261101 | Errors and printing errors are reserved.

BLOPL 1300 >80

BLOPL1300024DC08020840000W05
Article no.: 101972

BETTER LIGHT

Ambient/storage temperature [°C]	0 ... + 60
Operation temperature at Tc [°C]	- 5 ... + 60
Ambient temperature during operating [°C]	- 20 ... + 45
Rated life time L80/B10 at 25 °C [h]	60000

PACKAGING INFORMATION

EAN	4250716938715
Article no.	101972
Net weight [g]	49
Gross weight [g]	175
Gross width [mm]	200.0
Gross height [mm]	18.0
Gross length [mm]	200.0
Customs tariff number	94054099
Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	5000
State of origin	AT

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261101 | Errors and printing errors are reserved.