
## BLOPL 2000 >80

#### BLOPL2000024DC11920830000W20

Article no.: 101987









Lamp voltage



Max. length



Colour rendering index CRI Luminous flux per meter



#### **TENDER TEXT**

BL ONE+ 2000 LED strip 24VDC 11,9W/m IP20 CRI>80 3000K WHITE 20m LED module BLOPL 2000 >80 Article 101987 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45  $^{\circ}$ C at a service life of 60000 h . The BLOPL 2000 >80 LED-strip has a luminous flux of 1940 lm at 11.9 W, resulting in an efficiency of 163 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 6000 mm can be achieved. In terms of lighting, the module has a colour temperature of 3000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 6.25 mm. Degree of protection IP20 Dimension (L x W x H): 20000.0 mm x 8.0 mm x 1.5 mm

#### **TOP-FEATURES**

// Improvement of homogeneity by 20 additional LEDs per meter

//\_\_ Wide choice of light colors and lumen packages

//\_\_ Wide range of applications for linear lighting in

//\_\_ With a maximum module length of up to 6000 mm long, linear lighting lines can be implemented















# BLOPL 2000 >80

### BLOPL2000024DC11920830000W20

Article no.: 101987



### MECHANICAL DATA

Width [mm]	3.0
Length [mm]	20000.0
Height/depth [mm]	1.5
Height [mm]	1.5
Colour	White
Model	Band
Self-adhesive y	/es
Lamp type	LED nicht austauschbar
Distance [mm]	5.25
Distance relating to	.ED zu LED
Degree of protection (IP)	P20
Length of particular segments [mm]	50.0
Lowest bending radius [mm]	20
With connection set y	/es
With end piece	nein
Number of lamps per meter 1	160

## **ELECTRICAL DATA**

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Lamp power per meter [W]	11.9
Overall efficiency [lm/W]	163

## LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Colour temperature [K]	3000
Colour of light	White
Luminous flux per meter [lm]	1940
Energy efficiency class provided exchangeable built-in lamp	D
Colour consistency (McAdam ellipse)	SDCM3

## CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	2
Max. length [mm]	6000

## TEMPERATURE TECHNICAL DATA

## BLOPL 2000 >80

#### BLOPL2000024DC11920830000W20

Article no.: 101987



Ambient/storage temperature [°C]	0+60
Operation temperature at Tc [°C]	- 5 + 60
Ambient temperature during operating [°C]	- 20 + 45
Rated life time L80/B10 at 25 °C [h]	60000

### PACKAGING INFORMATION

EAN	4250716938869
Article no.	101987
Net weight [g]	199
Gross weight [g]	319
Gross width [mm]	200.0
Gross height [mm]	18.0
Gross length [mm]	200.0
Customs tariff number	94054099
Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	20000
State of origin	AT

<sup>\*</sup> Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at