
BL AIR TOP 450 EOL

BL AIR Top LED ligth tube 450lm/m 24VDC 7.2W/m IP67 840 5m

Article no.: 102110




















Colour rendering index CRI Luminous flux per meter



TENDER TEXT

AIR TOP LED ligth tube, LED strip in silicone sheath, 450 lm/m, wave-shaped bend to light emission surface, cable connection on one side, cable outlet at bottom, 24VDC 7.2W/m IP67 CRI>80 4000K WHITE 5m LED module BL AIR TOP 450 EOL Article 102110 The BL AIR TOP 450 EOL LED light tube has a luminous flux of 450 lm at a power of 7.2 W, which results in an efficiency of 63 lm/W. With a nominal voltage of 24 V DC at the connection, a maximum module length of 5010 mm can be achieved. In terms of lighting, the module has a color temperature of $\bar{4000}$ K and a beam angle of 120°. All with a color rendering index of >80 and a binning selection according to SDCM3 (MacAdams). The light strip can be divided every 50.0 mm, resulting in an LED spacing of 7.14 mm. Protection class IP67, Smallest possible bending radius 200 mm. At an ambient temperature of 85°C, a service life of 50,000 hours can still be guaranteed. Up to 95°C, the service life is 30,000 hours and at temperatures of 100°C it is still 16,000 hours (> L70B50). Dimensions (L x W x H): 5010.0 mm x 13.2 mm x 12.0 mm

TOP-FEATURES

// Homogeneously luminous light line without visible light points

//__ IP67 -protection in highly flexible silicone jacket

//_ New connection: the end caps close straight to the

BL AIR TOP 450 EOL

BL AIR Top LED ligth tube 450lm/m 24VDC 7.2W/m IP67 840 5m

Article no.: 102110



MECHANICAL DATA

Width [mm]	13.2
Length [mm]	5010.0
Height/depth [mm]	12
Height [mm]	12.0
Colour	White
Model	Schlauch
Self-adhesive	nein
Lamp type	LED nicht austauschbar
Distance [mm]	7.14
Distance relating to	LED zu LED
Degree of protection (IP)	IP67
Length of particular segments [mm]	50.0
Lowest bending radius [mm]	200
Number of lamps per meter	140

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Lamp power per meter [W]	7.2
Overall efficiency [lm/W]	63

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Colour temperature [K]	4000
Colour of light	White
Luminous flux per meter [lm]	450
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	2
Max. length [mm]	5010

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	- 20 + 55
Ambient temperature during operating [°C]	- 20 + 55
Rated life time L80/B10 at 25 °C [h]	50000

BL AIR TOP 450 EOL

BL AIR Top LED ligth tube 450lm/m 24VDC 7.2W/m IP67 840 5m

Article no.: 102110



PACKAGING INFORMATION

Article no.	102110
Net weight [g]	0.609
Gross weight [g]	0.609
Gross width [mm]	330.0
Gross height [mm]	27.0
Gross length [mm]	330.0
Customs tariff number	94054039
Net width [mm]	13.2
Net height [mm]	12
Net length [mm]	5010
State of origin	AT

^{*} Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at