


BL AIR48 Aura Top 10W

BL AIR48 Aura Top LED light tube 730lm/m 48VDC 10W/m IP67 940 100m

Article no.: 172320



48

V

Lamp voltage

20000

mm

Max. length

>90

Colour rendering index CRI

730

lm

Luminous flux per meter

TENDER TEXT

LED light tube AIR48 Aura Top 730lm/m, silicone, 48 VDC, 10W/m, 73 lm/W, IP67 (without dark areas), CRI >90, 4000 K, one-sided cable 50 cm, cable exit bottom, 100 meters LED module BL AIR48 Aura Top 10W Article 172320 The BL AIR48 Aura Top 10W is a linear LED light strip in a highly flexible silicone sheath. The LED module can be bent in a wave shape in the direction of the light exit surface. It is resistant to salt solution, acid and alkali corrosion. It is flame-retardant and UV-resistant. Suitable for ambient temperatures of -40 ... +60 °C with a service life of 84000 h . The BL AIR48 Aura Top 10W LED light strip has a luminous flux of 730 lm at an output of 10.0 W, which results in an efficiency of 73 lm/W. With a nominal voltage of 48 V DC at the connection, a maximum module length of 20000 mm can be achieved. In terms of lighting, the module has a color temperature of 4000 K and a beam angle of 114°. All with a color rendering index of >90 . The light strip can be divided every 100.0 mm, which results in an LED spacing of 3.125 mm. Protection class IP67 . Smallest possible bending radius 60 mm Dimensions (L x W x H): 100000.0 mm x 13.0 mm x 12 mm

TOP-FEATURES

//__ Salt solution resistance, acid and alkali corrosion resistance, flame retardant resistance, UV resistance

//__ No dark spots

//__ Protection class IP67

//__ Product application: Sign lighting, decorative outdoor/indoor lighting, architectural contour application

48 V

>90

IP67

4000 K

BL AIR48 Aura Top 10W

BL AIR48 Aura Top LED light tube 730lm/m 48VDC 10W/m IP67 940 100m

Article no.: 172320



MECHANICAL DATA

Width [mm]	13.0
Length [mm]	100000.0
Height/depth [mm]	12
Model	Schlauch
UV-resistant	Yes
Self-adhesive	nein
Korrosionsbeständig	ja
Lamp type	LED nicht austauschbar
Impact strength	IK08
Distance [mm]	3.125
Distance relating to	LED zu LED
Degree of protection (IP)	IP67
Length of particular segments [mm]	100.0
Lowest bending radius [mm]	60
Number of lamps per meter	320

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	48
Lamp power per meter [W]	10.0
Overall efficiency [lm/W]	73

LIGHT TECHNICAL DATA

Beam angle [°]	114
Colour rendering index CRI	>90
Colour temperature [K]	4000
Colour of light	White
Luminous flux per meter [lm]	730
Colour consistency (McAdam ellipse)	SDCM5

CONNECTION

Number of poles	2
Max. length [mm]	20000

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	0 ... + 60
Impact strength	IK08
Ambient temperature during operating [°C]	- 40 ... + 60
Rated life time L70/B50 at 25 °C [h]	84000

BL AIR48 Aura Top 10W

BL AIR48 Aura Top LED light tube 730lm/m 48VDC 10W/m IP67 940 100m

Article no.: 172320



PACKAGING INFORMATION

EAN	4250716955323
Article no.	172320
Customs tariff number	9405423190
Net width [mm]	13.0
Net height [mm]	12
Net length [mm]	100000
State of origin	CN

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of $\pm 10\%$ (or $\pm 15\%$ at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article	Article no.
BL mounting set silver for Neon Top 25mm	171866
BL end cap set white for NEON Top	171868
BL built-up profile for NEON TOP	171286
BL mounting set silver for Neon Top 25mm	171866
BL end cap set white for NEON Top	171868
BL built-up profile for NEON TOP	171286

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at