


COR Lite 890lm/m

BL COR Lite LED strip 890lm/m 24VDC 8.8W/m IP20 840 5m

Article no.: 171992



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter


TENDER TEXT

LED strip light COR Lite 890 lm/m 24VDC 8.8W/m 101lm/W IP20 CRI>80 4000K WHITE
1m connection cable on both sides including Dupont connector, 5 meters per box

TOP-FEATURES

//_ Hervorragendes Preis-Leistungs-Verhältnis

//_ Ideal für indirekte Beleuchtung



COR Lite 890lm/m

BL COR Lite LED strip 890lm/m 24VDC 8.8W/m IP20 840 5m

Article no.: 171992



MECHANICAL DATA

Width [mm]	8.0
Length [mm]	5000.0
Height/depth [mm]	1.5
Model	Band
Self-adhesive	Yes
Lamp type	LED nicht austauschbar
Distance [mm]	8.33
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments [mm]	50.0
With connection set	Yes
Number of lamps per meter	120

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Input voltage range [V]	23 - 25
Lamp power per meter [W]	8.8
Overall efficiency [lm/W]	101

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Colour temperature [K]	4000
Colour of light	White
Luminous flux per meter [lm]	890
Energy efficiency class provided exchangeable built-in lamp	F
Colour consistency (McAdam ellipse)	SDCM5

CONNECTION

Conductor cross section [mm ²]	0.32
Number of poles	2
Max. length [mm]	5000

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	0 ... + 60
Ambient temperature during operating [°C]	- 25 ... + 40
Rated life time L70/B50 at 25 °C [h]	20000

COR Lite 890lm/m

BL COR Lite LED strip 890lm/m 24VDC 8.8W/m IP20 840 5m

Article no.: 171992



PACKAGING INFORMATION

EAN	4250716951028
Article no.	171992
Net weight [g]	92
Gross weight [g]	92
Gross width [mm]	158.0
Gross height [mm]	13.5
Gross length [mm]	189.0
Customs tariff number	9405423990
Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	5000
State of origin	CN

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of +/- 10% (or +/- 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at