

# BL COR Pure COB 1600

**BL COR Pure COB LED-Strip 1510lm/m 24VDC 15W/m IP20 940 5m**

Article no.: 172066



---

## TENDER TEXT

LED-Lichtband COR Pure COB 1510lm/m 24VDC 15W/m 101lm/W IP20 CRI>90 4000K WHITE beidseitig 0,5m Anschlusskabel inkl. Dupont Stecker, 5 Meter/Rolle LED module BL COR Pure COB 1600 Article 172066 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Suitable for ambient temperatures from at a service life of . The BL COR Pure COB 1600 LED-strip has a luminous flux of at , resulting in an efficiency of . At a nominal voltage of on the connection, a maximum module length of can be achieved. In terms of lighting, the module has a colour temperature of and a beam angle of . All this with a colour rendering index of and a Binning selection based on (MacAdams). The light strip can be separated every , resulting in a LED distance of . Degree of protection Dimension (L x W x H): x x

---

# BL COR Pure COB 1600

**BL COR Pure COB LED-Strip 1510lm/m 24VDC 15W/m IP20 940 5m**

Article no.: 172066



**SAFETY INFORMATION:** Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

**DISCLAIMER OF WARRANTY:** The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)