

COR Pure Free 800

BL COR PURE FREE LED strip 755lm/m 24VDC 6W/m IP20 930 5m

Article no.: 172081



Degree of protection (IP)



Length of particular segments



Colour temperature




Luminous flux per meter

TENDER TEXT

LED strip light COR PURE FREE 755lm/m 24VDC 6W/m 126lm/W IP20 CRI>90 3000K WHITE 0.5m connection cable on both sides incl. Dupont plug, 5 meters/roll

TOP-FEATURES

- //_ LED strip, all 5.0 mm separable
- //_ Without soldering connection
- //_ 24 V-Single LED per cut for more flexible application



COR Pure Free 800

BL COR PURE FREE LED strip 755lm/m 24VDC 6W/m IP20 930 5m

Article no.: 172081



MECHANICAL DATA

Width [mm]	8.0
Length [mm]	5000.0
Height [mm]	1.5
Model	Band
Self-adhesive	Yes
Lamp type	LED nicht austauschbar
Distance [mm]	5
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments [mm]	5.0
Number of lamps per meter	200

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Input voltage range [V]	23 - 25
Lamp power per meter [W]	6.0
Overall efficiency [lm/W]	126

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>90
Colour temperature [K]	3000
Colour of light	White
Luminous flux per meter [lm]	755
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section [mm ²]	0.5
Number of poles	2
Max. length [mm]	8000

TEMPERATURE TECHNICAL DATA

Ambient temperature during operating [°C]	- 25 ... + 40
Rated life time L70/B50 at 25 °C [h]	60000
Rated life time L80/B10 at 25 °C [h]	60000

PACKAGING INFORMATION

COR Pure Free 800

BL COR PURE FREE LED strip 755lm/m 24VDC 6W/m IP20 930 5m

Article no.: 172081



EAN	4250716952322
Article no.	172081
Net weight [g]	90
Gross weight [g]	120
Gross width [mm]	203.0
Gross height [mm]	17.0
Gross length [mm]	230.0
Customs tariff number	9405423990
Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	5000
State of origin	CN

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at