
# BL COR Pure 1300

#### BL COR Pure LED strip 1390lm/m 24VDC 8.7W/m IP20 840 5m

Article no.: 171850





### **TENDER TEXT**

LED light strip COR Pure 1390 lm/m 24VDC 8.7W/m 160lm/W IP20 CRI>80 4000K, WHITE Colors and BLT label, one-sided connection cable 50 cm, 5 meters LED module BL COR Pure 1300 Article 171850 The BL COR Pure 1300 LED-strip has a luminous flux of 1390 lm at 8.7 W, resulting in an efficiency of 160 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 5000 mm can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 62.5 mm, resulting in a LED distance of 7.81 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.6 mm

### **TOP-FEATURES**

//\_\_ Luminance efficiency up to 160 lm/W

//\_\_ Life span up to 60000 h



# BL COR Pure 1300

## BL COR Pure LED strip 1390lm/m 24VDC 8.7W/m IP20 840 5m

Article no.: 171850



#### MECHANICAL DATA

Width [mm]	8.0
Length [mm]	5000.0
Height [mm]	1.6
Colour	White
Model	Band
Self-adhesive	yes
Lamp type	LED nicht austauschbar
Distance [mm]	7.81
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments [mm]	62.5
Lowest bending radius [mm]	30
Number of lamps per meter	128

# **ELECTRICAL DATA**

Protection class	
Voltage type	DC
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Lamp power per meter [W]	8.7
Overall efficiency [lm/W]	160

# LIGHT TECHNICAL DATA

# CONNECTION

Number of poles	2
Max. length [mm]	5000

# TEMPERATURE TECHNICAL DATA

Ambient temperature during operating [°C]	0 + 60
Rated life time L70/B50 at 25 °C [h]	60000

# BL COR Pure 1300

#### BL COR Pure LED strip 1390lm/m 24VDC 8.7W/m IP20 840 5m

Article no.: 171850



#### PACKAGING INFORMATION

EAN	4250716948684
Article no.	171850
Net weight [g]	100
Gross weight [g]	118
Gross width [mm]	242.0
Gross height [mm]	10.0
Gross length [mm]	266.0
Customs tariff number	9405423990
Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	5000
State of origin	CN

<sup>\*</sup> Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at