


# BL COR Pure 900

BL COR Pure LED strip 900lm/m 24VDC 9.6W/m IP20 827 50m  
Article no.: 171325



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

## TENDER TEXT

LED strip COR Pure 900 lm/m 24VDC 9.6W/m 93lm/W IP20 CRI>80 2700K WHITE, Colors label, without connection cable, 50 meters/box LED module BL COR Pure 900 Article 171325 The BL COR Pure 900 LED-strip has a luminous flux of 900 lm at 9.6 W, resulting in an efficiency of 93 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 5000 mm can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 117°. All this with a colour rendering index of >80 and a Binning selection based on (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 8.33 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

## TOP-FEATURES

- //\_\_ Luminance efficiency up to 93 lm/W
- //\_\_ Life span up to 36000 h
- //\_\_ Separability 50.0 mm

24 V	>80	IP20	2700 K
------	-----	------	--------

# BL COR Pure 900

BL COR Pure LED strip 900lm/m 24VDC 9.6W/m IP20 827 50m

Article no.: 171325



## MECHANICAL DATA

Width [mm]	8.0
Length [mm]	50000.0
Height/depth [mm]	1.5
Height [mm]	1.5
Colour	White
Model	Band
Self-adhesive	yes
Lamp type	LED nicht austauschbar
Distance [mm]	8.33
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments [mm]	50.0
Lowest bending radius [mm]	30
Number of lamps per meter	120

## ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Lamp power per meter [W]	9.6
Overall efficiency [lm/W]	93

## LIGHT TECHNICAL DATA

Beam angle [°]	117
Colour rendering index CRI	>80
Rated luminous flux according to IEC 62722-2-1 [lm]	900
Colour temperature [K]	2700
Colour of light	White
Luminous flux per meter [lm]	900
Energy efficiency class of the built-in lamp	F

## CONNECTION

Number of poles	2
Max. length [mm]	5000

## TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	0 ... + 60
Ambient temperature during operating [°C]	- 25 ... + 40
Rated life time L70/B50 at 25 °C [h]	36000

# BL COR Pure 900

**BL COR Pure LED strip 900lm/m 24VDC 9.6W/m IP20 827 50m**

Article no.: 171325



## PACKAGING INFORMATION

EAN	4250716948585
Article no.	171325
Net weight [g]	920
Gross weight [g]	920
Gross width [mm]	80.0
Gross height [mm]	210.0
Gross length [mm]	210.0
Customs tariff number	9405423990
Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	50000
State of origin	CN

\* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR ). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

**SAFETY INFORMATION:** Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

**DISCLAIMER OF WARRANTY:** The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)