




BL COR Skyline

BL COR Skyline LED light system 1320lm/m 24VDC 13.5W/m IP20 940 6m black
Article no.: 171595



Length



Colour housing



Lamp type




Light exit

TENDER TEXT

Skyline black LED lighting system with LED strip 1320 lm/m and mounting material 24VDC 13.5W/m 98lm/W IP20 CRI>90 4000K WHITE, Colors and BLT label 6 metres LED Module BL COR Skyline Item 171595 Linear LED strip light on steel tape with movable mounting modules and cable for easy assembly and quick installation. The BL COR Skyline LED strip light has a luminous flux of 1320 lm with a power of 13.5 W, giving an efficiency of 98 lm/W. With a nominal voltage of 24 V DC at the connection. In terms of lighting, the module has a color temperature of 4000 K and a beam angle of 120°. All with a color rendering index of >90 . The light strip can be divided every 50.0 mm, resulting in an LED spacing of 8.33 mm. Protection class IP20 . Dimensions (L x W x H): 6000.0 mm x 35.0 mm x 130 mm

TOP-FEATURES

- //__ The flexible rotation axis offers a wide range of angles
- //__ Innovative aluminum strip solution with integrated LED strip
- //__ Simple configuration - cut to length, plug in - done
- //__ Replaceable LED strips up to 13.5 W Watt



BL COR Skyline

BL COR Skyline LED light system 1320lm/m 24VDC 13.5W/m IP20 940 6m black

Article no.: 171595



MECHANICAL DATA

Colour housing	Black
Width [mm]	35.0
Length [mm]	6000.0
Height/depth [mm]	130
With movement sensor	nein
With switch	nein
Lamp type	LED austauschbar
Distance [mm]	8.33
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
With lamp	yes
Length of particular segments [mm]	50.0
Control gear included	nein
Suspension included in delivery	yes
Light distributor	ohne

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Nominal voltage [V]	24
Overall efficiency [lm/W]	98
Max. system power [W]	13.5

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>90
Light exit	direct / indirect
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	1320
Colour temperature [K]	4000
Colour of light	White

CONNECTION

Electrical connection with connector system	yes
---	-----

PACKAGING INFORMATION

EAN	4250716948615
Article no.	171595
Net weight [g]	2000
Gross weight [g]	2000

BL COR Skyline

BL COR Skyline LED light system 1320lm/m 24VDC 13.5W/m IP20 940 6m black

Article no.: 171595



Gross width [mm]	352.0
Gross height [mm]	70.0
Gross length [mm]	346.0
Customs tariff number	94059900
Net width [mm]	35.0
Net height [mm]	130
Net length [mm]	60000
State of origin	CN

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article

Article no.

171864

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at