


Ceiling & wall luminaires Comfort

BL CWL Comfort Luminaire Q500mm 4000lm 34W 110D/I 840 white

Article no.: 730015




Beam angle



Suitable for emergency lighting



Height



Rated luminous flux according to IEC 62722-2-1

TENDER TEXT

Ceiling and wall luminaire, white, microprismatic cover, direct/indirect, incl. converter, 4000K, UGR Ceiling & wall luminaires Comfort Article 730015 LED ceiling and wall light with direct/indirect light distribution for a pleasant and homogeneous room experience. Installation option: Bajonettverschluss Light body made of high-quality Aluminium, which is coated with a White matt. The cover is made of Plastic Opal. Lumen 4000 lm with an efficiency of 117 lm/W and a color rendering of >80, total power 34 W, beam angle 110°, service life 50000 h, protection class IP20, UGR

TOP-FEATURES

- //__ Color temperature of 4000 K
- //__ In- and direct light component with asymmetrical illumination
- //__ Easy mounting due to Bajonettverschluss
- //__ Housing made of Aluminium White



Ceiling & wall luminaires Comfort

BL CWL Comfort Luminaire Q500mm 4000lm 34W 110D/I 840 white

Article no.: 730015



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width [mm]	500.0
Length [mm]	500.0
Height [mm]	96.0
Outer diameter [mm]	500
Mounting method	Aufbau
Reflector	matt
With movement sensor	nein
Lamp type	LED nicht austauschbar
Type of fastening	Bajonettverschluss
Direct/indirect components separately adjustable	nein
Suitable for emergency lighting	nein
Material of the cover	Plastic Opal
Degree of protection (IP)	IP20
With lamp	Yes
Surface finishing	matt
Control gear included	Yes
Unified Glare Ratio (UGR)	<25

ELECTRICAL DATA

Protection class	III
Voltage type	AC
Max. inrush current [A]	24.7
Nominal voltage [V]	220 - 240
Operating frequency [Hz]	50 / 60
Type of dimming	Not dimmable
Overall efficiency [lm/W]	117
Nennstrom [A]	0,224
Max. system power [W]	34
Power factor	0.95
No dim function	Yes
Flicker percent (< 165 Hz)	<5

LIGHT TECHNICAL DATA

Function	ohne
Beam angle [°]	110
Colour rendering index CRI	>80
Light exit	direct / indirect
Light distribution	symmetrical / asymmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	4000

Ceiling & wall luminaires Comfort

BL CWL Comfort Lumininaire Q500mm 4000lm 34W 110D/I 840 white

Article no.: 730015



Colour temperature [K]	4000
Colour of light	White
Energy efficiency class of the built-in lamp	F

TEMPERATURE TECHNICAL DATA

Ambient temperature during operating [°C]	- 20 ... + 40
Rated life time L80/B10 at 25 °C [h]	50000

PACKAGING INFORMATION

EAN	9009453015662
Article no.	730015
Net weight [g]	5645
Gross weight [g]	6230
Net width [mm]	500.0
Net height [mm]	96
Net length [mm]	500
State of origin	CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at