

BL Ceiling & wall luminaires Pure

BL CWL Pure surface-mounted luminaire 300mm 1900lm 18W 120D 830/40/57 WH IP54

Article no.: 732000



With movement sensor



Impact strength



Degree of protection (IP)



Max. system power


TENDER TEXT

Ceiling and wall luminaire, white, microprismatic cover, direct, incl. converter, Color Change 3000K + 4000K + 5700K, dimensions: 300x58mm BL Ceiling & wall luminaires Pure Article 732000 The perfect solution for lighting hallways and stairwells in private or public areas. The desired light color (3000 & 4000 & 5700 K) can be set directly on the LED light. Housing Kunststoff White Fastening using Haltebügel auf der Rückseite . With integrated motion detector - nein . Luminous flux 1900 lm with an efficiency of 106 lm/W and a color rendering of >80 , total power 18 W, beam angle 120°, service life 50000 h , protection class IP54 , UGR

TOP-FEATURES

// __ Quick installation with 3-pole plug-in clip and Haltebügel auf der Rückseite

// __ Homogeneous light distribution over the entire light emission surface



BL Ceiling & wall luminaires Pure

BL CWL Pure surface-mounted luminaire 300mm 1900lm 18W 120D 830/40/57 WH IP54

Article no.: 732000



MECHANICAL DATA

Material housing	Kunststoff
Colour housing	White
Width [mm]	300.0
Length [mm]	300.0
Height [mm]	58.0
Diameter [mm]	300
Outer diameter [mm]	300
Mounting method	Aufbau
UV-resistant	yes
With movement sensor	nein
Lamp type	LED nicht austauschbar
Type of fastening	Haltebügel auf der Rückseite
Material of the cover	Plastic opal
Impact strength	IK08
Degree of protection (IP)	IP54
With lamp	yes
Control gear included	yes
Unified Glare Ratio (UGR)	<25

ELECTRICAL DATA

Protection class	III
Voltage type	AC
Max. inrush current [A]	9.8
Nominal voltage [V]	220 - 240
Operating frequency [Hz]	50 / 60
Type of dimming	not dimmable
Overall efficiency [lm/W]	106
Nennstrom [A]	0,783
Max. system power [W]	18
Power factor	0.9
No dim function	yes
Flicker percent (< 165 Hz)	<5

LIGHT TECHNICAL DATA

Function	Farbwechsel
Beam angle [°]	120
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	1900
Colour temperature [K]	3000 & 4000 & 5700

BL Ceiling & wall luminaires Pure

BL CWL Pure surface-mounted luminaire 300mm 1900lm 18W 120D 830/40/57 WH IP54

Article no.: 732000



Colour of light White

Energy efficiency class of the built-in lamp F

CONNECTION

Connection type 3 - pole plug - in clip

TEMPERATURE TECHNICAL DATA

Impact strength IK08

Ambient temperature during operating [°C] - 20 ... + 40

Rated life time L70/B10 at 25 °C [h] 50000

PACKAGING INFORMATION

EAN 9009453013828

Article no. 732000

Net weight [g] 760

Gross weight [g] 1130

Net width [mm] 300.0

Net height [mm] 58

Net length [mm] 300

State of origin CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at