



Ceiling- & Wall luminiare Trend

BL CWL Trend+ surface/pendant lum. 435mm 4400lm 40W 90D/I 830-840 black DALI


Article no.: 731021



Colour housing



Type of dimming




Rated luminous flux
according to IEC
62722-2-1

TENDER TEXT

CWL LED pendant luminaire, 4,400 lumens, 40W, 90° direct/indirect illumination, CRI >80, 3,000- 4,000 Kelvin, IP20, protection class I, DALI dimmable, UGR Ceiling- & Wall luminaire Trend Article 731021 Modern surface lights with a wide range of possible uses for representative environments. Whether as a wall or ceiling-mounted version with direct/indirect light component. Mounting type . The color temperature 3000-4000 K can be selected via dip switch. Housing Aluminium Black , Cover material Plastic structured , Luminous flux 4400 lm with an efficiency of 110 lm/W and a color rendering of >80 , Total power 40 W, Beam angle 90°, Service life 50000 h, Protection class IP20 , UGR

TOP-FEATURES

- //__ Color temperature selectable via dip switch 3000-4000 K
- //__ Light emission direct/indirect
- //__ Housing Aluminium Black



Ceiling- & Wall luminiare Trend

BL CWL Trend+ surface/pendant lum. 435mm 4400lm 40W 90D/I 830-840 black DALI

Article no.: 731021



MECHANICAL DATA

Material housing	Aluminium
Colour housing	Black
Width [mm]	435.0
Length [mm]	435.0
Height [mm]	91.0
Diameter [mm]	435
With movement sensor	nein
Type of control gear	LED - Betriebsgerät stromgesteuert
Lamp type	LED nicht austauschbar
Material of the cover	Plastic structured
Degree of protection (IP)	IP20
Suspension included in delivery	nein
Unified Glare Ratio (UGR)	<19

ELECTRICAL DATA

Protection class	I
Voltage type	AC
Nominal voltage [V]	200 - 240
Type of dimming	DALI
Overall efficiency [lm/W]	110
Max. system power [W]	40
Power factor	0.9

LIGHT TECHNICAL DATA

Beam angle [°]	90
Colour rendering index CRI	>80
Light exit	direct / indirect
Light distribution	symmetrisch
Rated luminous flux according to IEC 62722-2-1 [lm]	4400
Colour temperature [K]	3000 - 4000
Colour of light	White

TEMPERATURE TECHNICAL DATA

Rated life time L90/B50 at 25 °C [h]	50000
--------------------------------------	-------

PACKAGING INFORMATION

EAN	4250716949377
Article no.	731021
Net weight [g]	3590
Gross weight [g]	5240

Ceiling- & Wall luminiare Trend

BL CWL Trend+ surface/pendant lum. 435mm 4400lm 40W 90D/I 830-840 black DALI

Article no.: 731021



Gross width [mm]	510.0
Gross height [mm]	130.0
Gross length [mm]	510.0
Customs tariff number	94051098
Net width [mm]	435.0
Net height [mm]	91
Net length [mm]	435
State of origin	CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at