
BL Downlight Protected

BL DL Xtreme 228 3300LM/60D/840 DALI WH


Article no.: 723009













Impact strength





Degree of protection (IP) Unified Glare Ratio (UGR)

TENDER TEXT

Einbaudownlight rund, inkl. Konverter DALI, 4000K, IP54, UGR BL Downlight Protected Article 723009 BL Downlight Protected LED downlight with easy installation and commissioning of the LED converter thanks to pre-installed connection cable; highly efficient reflector made of Aluminium; high-quality, White aluminum cooling housing; excellent thermal management; suitable for ambient temperatures of-20 ... +45 °C; protection class IP54 roomside; impact resistance IK06; protection class III; service life (50000 h;); Luminaire luminous flux 3300 lm; Connected load 17 W; Luminaire luminous efficacy 100 lm/W; Colour rendering >80; Light color White; Colour temperature 4000 K; Beam angle 60°; Flicker-free (

TOP-FEATURES

// Excellent glare value of UGR

//__ Aluminum reflector with mirror optics§

// Protection class (room side) IP54

//__ Plug&Play Connection

BL Downlight Protected

BL DL Xtreme 228 3300LM/60D/840 DALI WH

Article no.: 723009



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width [mm]	228.0
Length [mm]	228.0
Height/depth [mm]	99
Outer diameter [mm]	228
Mounting method	Einbau
Reflector	Silber
Lamp type	LED nicht austauschbar
Type of fastening	Retaining springs
Impact strength	IK06
Degree of protection (IP)	IP54
With lamp	yes
Surface finishing	matt
Suitable for wall mounting	yes
Control gear included	yes
Suitable for ceiling mounting	yes
Unified Glare Ratio (UGR)	<22

ELECTRICAL DATA

age type AC	
er factor 0,95	
ninal voltage [V] 220 - 240	
rating frequency [Hz] 50 / 60	
e of dimming DALI	
rall efficiency [lm/W] 100	
nstrom [A] 0,143	
. system power [W] 29	
ming DALI yes	
ter percent (< 165 Hz) <10	

LIGHT TECHNICAL DATA

Beam angle [°]	60
Colour rendering index CRI	>80
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	3300
Colour temperature [K]	4000
Colour of light	White
Energy efficiency class of teh built-in lamp	G
Flicker-free	yes

BL Downlight Protected

BL DL Xtreme 228 3300LM/60D/840 DALI WH

Article no.: 723009



TEMPERATURE TECHNICAL DATA

Impact strength	IK06
Ambient temperature during operating [°C]	- 20 + 45
Rated life time L70/B10 at 25 °C [h]	50000

PACKAGING INFORMATION

EAN	9009453033796
Article no.	723009
Net weight [g]	1135
Gross weight [g]	1305
Net width [mm]	228.0
Net height [mm]	99
Net length [mm]	228
State of origin	CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at