



BL Downlight Pure Flat

BL Downlight Pure recessed luminaire 180mm 1400lm 12.5W 110D 840white IP44 350mA

Article no.: 722030



Height/depth



UV-resistant



Impact strength



Degree of protection (IP)

TENDER TEXT

LED recessed downlight round, 1,400 lumen, 12.5W, 110° direct beam, CRI >80, 4,000 Kelvin, IP44, IK05, protection class III, dimmable, UV-resistant, EEK F, white aluminium housing, without power supply unit, dimensions: D 180mm x H 24mm BL Downlight Pure Flat Article 722030 LED ceiling recessed downlight - power supply nein - with Retaining springs for ceiling thicknesses of 10 - 20 mm; use when space in the ceiling is limited; high-quality, White coated Aluminium frame; best light quality and homogeneous Symmetrical light distribution across the entire light emission surface; UV-resistant Yes ; protection class IP44 ; Shock resistance IK05 , Luminous flux 1400 lm, Connected load 12.5 W, Luminaire luminous efficacy 112 lm/W, Color rendering >80 , Light color White , Color temperature 4000 K, Beam angle 110°, Dimensions: 180 mm x 24 mm, Ceiling cutout 165 mm

TOP-FEATURES

- //_ Light color 4000 K
- //_ IP44 splash-proof
- //_ Plug&Play connection
- //_ Extra-flat design



BL Downlight Pure Flat

BL Downlight Pure recessed luminaire 180mm 1400lm 12.5W 110D 840white IP44 350mA

Article no.: 722030



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width [mm]	180.0
Length [mm]	180.0
Height/depth [mm]	24
Installation diameter [mm]	165
Outer diameter [mm]	180
Mounting method	Einbau
UV-resistant	Yes
Lamp type	LED nicht austauschbar
Type of fastening	Retaining springs
Impact strength	IK05
Degree of protection (IP)	IP44
With lamp	Yes
Surface finishing	matt
Suitable for wall mounting	Yes
Control gear included	nein
Suitable for ceiling mounting	Yes

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Nominal voltage [V]	37 - 40
Overall efficiency [lm/W]	112
Nennstrom [A]	0,35
Max. system power [W]	12.5
Dimming depending on control gear	Yes

LIGHT TECHNICAL DATA

Beam angle [°]	110
Colour rendering index CRI	>80
Light distribution	Symmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	1400
Colour temperature [K]	4000
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM4
Flicker-free	Yes

TEMPERATURE TECHNICAL DATA

Impact strength	IK05
-----------------	------

BL Downlight Pure Flat

BL Downlight Pure recessed luminaire 180mm 1400lm 12.5W 110D 840white IP44 350mA

Article no.: 722030



Ambient temperature during operating [°C]	- 20 ... + 40
Rated life time L80/B10 at 25 °C [h]	50000

PACKAGING INFORMATION

EAN	4250716953268
Article no.	722030
Net weight [g]	300
Gross weight [g]	341
Customs tariff number	94054239
Net width [mm]	180.0
Net height [mm]	24
Net length [mm]	180
State of origin	CN

NECESSARY ACCESSORIES

Article	Article no.
LED DRIVER 220-240V CC 350mA 27-45VDC ON/OFF	729178
LED DRIVER 220-240V CC 350mA 9-45VDC DALI	729179

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at