



# BL Downlight Pure Flat

**BL Downlight Pure recessed luminaire 240mm 2200lm 18.5W 110D 830 WH IP44 700mA**

Article no.: 722016



White

Colour housing

yes

UV-resistant

IP44

Degree of protection (IP)

## TENDER TEXT

LED recessed downlight round, 2,200 lumen, 18.5W, 110° direct beam, CRI >80, 3,000 Kelvin, IP44, IK05, protection class III, non-dimmable, UV-resistant, white aluminium housing, without power supply unit, dimensions: D 240mm x H 24mm BL Downlight Pure Flat Article 722016 LED ceiling recessed downlight - power supply nein - with Retaining springs for ceiling thicknesses of 10 - 20 mm; use when space in the ceiling is limited; high-quality, White coated Aluminium frame; best light quality and homogeneous light distribution across the entire light emission surface; UV-resistant; protection class IP44; Shock resistance IK05, Luminous flux 2200 lm, Connected load 18.5 W, Luminaire luminous efficacy 119 lm/W, Color rendering >80, Light color White, Color temperature 3000 K, Beam angle 119 lm/W, Ambient temperature, Dimensions: 240 mm x 24 mm, Ceiling cutout

## TOP-FEATURES

- //\_\_ Choice of light color from 3000 K
- //\_\_ IP44 splash-proof
- //\_\_ Available in round and square versions
- //\_\_ Plug&Play connection

>80

IP44

3000 K

# BL Downlight Pure Flat

**BL Downlight Pure recessed luminaire 240mm 2200lm 18.5W 110D 830 WH IP44 700mA**

Article no.: 722016



## MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width [mm]	240.0
Length [mm]	240.0
Height/depth [mm]	24
Outer diameter [mm]	240
UV-resistant	yes
Lamp type	LED nicht austauschbar
Type of fastening	Retaining springs
Impact strength	IK05
Degree of protection (IP)	IP44
With lamp	yes
Surface finishing	matt
Suitable for wall mounting	yes
Control gear included	nein
Suitable for ceiling mounting	yes

## ELECTRICAL DATA

Protection class	III
Voltage type	DC
Nominal voltage [V]	27 - 30
Overall efficiency [lm/W]	119
Nennstrom [A]	0,7
Max. system power [W]	18.5
Dimming depending on control gear	yes

## LIGHT TECHNICAL DATA

Beam angle [°]	110
Colour rendering index CRI	>80
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	2200
Colour temperature [K]	3000
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM4
Flicker-free	yes

## TEMPERATURE TECHNICAL DATA

Impact strength	IK05
Ambient temperature during operating [°C]	- 20 ... + 40
Rated life time L80/B10 at 25 °C [h]	50000

# BL Downlight Pure Flat

**BL Downlight Pure recessed luminaire 240mm 2200lm 18.5W 110D 830 WH IP44 700mA**  
Article no.: 722016



## PACKAGING INFORMATION

Article no.	722016
Net weight [g]	520
Gross weight [g]	601
Net width [mm]	240.0
Net height [mm]	24
Net length [mm]	240
State of origin	CN

## NECESSARY ACCESSORIES

Article	Article no.
	<b>729041</b>

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)