
BL Downlight Pure Flat

BL Downlight Pure recessed luminaire 240mm 2200lm 18.5W 110D 830white IP44 700mA
Article no.: 722029





WAGO Winsta© ready

24 mm	Yes	IK05	IP44
Height/depth	UV-resistant	Impact strength	Degree of protection (IP)

TENDER TEXT

LED recessed downlight round, 2,200 lumen, 18.5W, 110° direct beam, CRI >80, 3,000 Kelvin, IP44, IK05, protection class III, non-dimmable, UV-resistant, white aluminium housing, without power supply unit, dimensions: D 240mm x H 24mm BL Downlight Pure Flat Article 722029 LED ceiling recessed downlight - power supply nein - with Retaining springs for ceiling thicknesses of 10 - 20 mm; use when space in the ceiling is limited; high-quality, White coated Aluminium frame; best light quality and homogeneous Symmetrical light distribution across the entire light emission surface; UV-resistant Yes ; protection class IP44 ; Shock resistance IK05 , Luminous flux 2200 lm, Connected load 18.5 W, Luminaire luminous efficacy 119 lm/W, Color rendering >80 , Light color White , Color temperature 3000 K, Beam angle 110°, Dimensions: 240 mm x 24 mm, Ceiling cutout

TOP-FEATURES

//__ Light color 3000 K
//__ IP44 splash-proof
//__ Plug&Play connection
//__ Extra-flat design

>80 | IP44 | 3000 K

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261104 | Errors and printing errors are reserved.

BL Downlight Pure Flat

BL Downlight Pure recessed luminaire 240mm 2200lm 18.5W 110D 830white IP44 700mA
Article no.: 722029

BETTER LIGHT

MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width [mm]	240.0
Length [mm]	240.0
Height/depth [mm]	24
Outer diameter [mm]	240
UV-resistant	Yes
Lamp type	LED nicht austauschbar
Type of fastening	Retaining springs
Impact strength	IK05
Degree of protection (IP)	IP44
With lamp	Yes
Surface finishing	matt
Suitable for wall mounting	Yes
Control gear included	nein
Suitable for ceiling mounting	Yes

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Nominal voltage [V]	27 - 30
Overall efficiency [lm/W]	119
Nennstrom [A]	0,7
Max. system power [W]	18.5
Dimming depending on control gear	Yes

LIGHT TECHNICAL DATA

Beam angle [°]	110
Colour rendering index CRI	>80
Light distribution	Symmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	2200
Colour temperature [K]	3000
Colour of light	White
Energy efficiency class of teh built-in lamp	E
Colour consistency (McAdam ellipse)	SDCM4
Flicker-free	Yes

TEMPERATURE TECHNICAL DATA

Impact strength	IK05
Ambient temperature during operating [°C]	- 20 ... + 40

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261104 | Errors and printing errors are reserved.

BL Downlight Pure Flat

BL Downlight Pure recessed luminaire 240mm 2200lm 18.5W 110D 830white IP44 700mA
Article no.: 722029

Rated life time L80/B10 at 25 °C [h]	50000

PACKAGING INFORMATION

EAN	4250716953091
Article no.	722029
Net weight [g]	520
Gross weight [g]	615
Gross width [mm]	250.0
Gross height [mm]	40.0
Gross length [mm]	285.0
Customs tariff number	94054239
Net width [mm]	240.0
Net height [mm]	24
Net length [mm]	240
State of origin	CN

NECESSARY ACCESSORIES

Article	Article no.
LED DRIVER 220-240V CC 700mA 27-45VDC ON/OFF	729174
LED DRIVER 220-240V CC 700mA 9-45VDC DALI	729175

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at