


Drive Fixoutput

BL Drive Power supply unit CV 220-240VAC 100W 24VDC 4150mA IP20

Article no.: 170806



Output voltage range



Output power range



Degree of protection (IP)

TENDER TEXT

Constant voltage power supply unit. Input voltage 220-240VAC. Maximum total power 100W (max. 4.15A). Output voltage 24VDC. Protection class IP20. Protection class I. Dimensions LxWxH = 222x53x40mm BILTON LEDON Technology power supply Drive Fixoutput Article 170806 The power supply can be used up to 0-100 W output power and 24 V output voltage. The supply voltage of the power supply is 220 - 240 V and has a IP20 protection class and protection class I . Dimension (L x W x H): 222.0 mm x 53.0 mm x 40.0 mm



Drive Fixoutput

BL Drive Power supply unit CV 220-240VAC 100W 24VDC 4150mA IP20

Article no.: 170806



MECHANICAL DATA

| | |
|---------------------------------------|-------------------|
| Housing | Kunststoffgehäuse |
| Width [mm] | 53.0 |
| Length [mm] | 222.0 |
| Height [mm] | 40.0 |
| Mounting method | Aufbau |
| Colour | White |
| Model | Static |
| Control signal | ohne |
| With overheating protection | Yes |
| Suitable for outdoor use | nein |
| Degree of protection (IP) | IP20 |
| Core cross section [mm ²] | 0,5 - 2,5 |

ELECTRICAL DATA

| | |
|--|--------------|
| Protection class | I |
| Voltage type | AC |
| Control signal | ohne |
| With overheating protection | Yes |
| Input voltage range [V] | 220 - 240 |
| Output voltage range [V] | 24 |
| Output power range [W] | 0 - 100 |
| Output current range [mA] | 4150 |
| Type of dimming | Not dimmable |
| Overload protection | Yes |
| Suitable for constant current | Yes |
| Suitable for constant voltage | Yes |
| Suitable for DC-voltage (primary side) | nein |

CONNECTION

| | |
|---------------------------------------|-----------|
| Core cross section [mm ²] | 0,5 - 2,5 |
|---------------------------------------|-----------|

TEMPERATURE TECHNICAL DATA

| | |
|---|---------------|
| Ambient/storage temperature [°C] | - 40 ... + 70 |
| Operation temperature at Tc [°C] | - 10 ... + 70 |
| Ambient temperature during operating [°C] | - 20 ... + 45 |
| Lifespan at 20 °C [h] | 50000 |

PACKAGING INFORMATION

| | |
|-------------|---------------|
| EAN | 4250716929843 |
| Article no. | 170806 |

Drive Fixoutput

BL Drive Power supply unit CV 220-240VAC 100W 24VDC 4150mA IP20

Article no.: 170806



| | |
|-----------------------|------------|
| Net weight [g] | 286.8 |
| Gross weight [g] | 316.7 |
| Gross width [mm] | 55.0 |
| Gross height [mm] | 50.0 |
| Gross length [mm] | 225.0 |
| Customs tariff number | 8504408290 |
| Net width [mm] | 53.0 |
| Net height [mm] | 40 |
| Net length [mm] | 222 |
| State of origin | DE |

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at