BL High Bays Pure


BL HB Pure+ pendant luminaire 258mm 15000lm 100W 120D 850 230V

Article no.: 742091















Degree of protection (IP)



Control gear included



Rated luminous flux according to IEC 62722-2-1

TENDER TEXT

High bay luminaire made of black aluminium, incl. converter and ring bolt, 15000lm, 100W, 5000K, CRI80, 120° , IP65, IK08 Dimensions: D258x139mm BL High Bays Pure Article 742091 LED High Bay with integrated LED power supply - yes; Mounting type: Suspension using Seilabhängung, highly efficient lens optics, cooling housing Aluminium Black, excellent thermal management, suitable for ambient temperatures of -40...+60 °C, protection class IP65, shock resistance IK08, service life of 50000~h, luminous flux 15000~lm, connected load 100~W, color rendering >80, color temperature 5000~K, Beam angle 120° , Shock resistance IK08, Dimensions (D /H): $258~mm \times 139~mm$











BL High Bays Pure

BL HB Pure+ pendant luminaire 258mm 15000lm 100W 120D 850 230V

Article no.: 742091



MECHANICAL DATA

Colour housingBlackWidth [mm]258.0Length [mm]258.0Height/depth [mm]139Diameter [mm]258Mounting methodSuspensionType of control gearLED - Betriebsgerät stromgesteuertLamp typeLED nicht austauschbarType of fasteningSeilabhängungImpact strengthIK08Degree of protection (IP)IP65Control gear includedyesSuspension included in deliverynein	Material housing	Aluminium
Length [mm]258.0Height/depth [mm]139Diameter [mm]258Mounting methodSuspensionType of control gearLED - Betriebsgerät stromgesteuertLamp typeLED nicht austauschbarType of fasteningSeilabhängungImpact strengthIK08Degree of protection (IP)IP65Control gear includedyes	Colour housing	Black
Height/depth [mm]139Diameter [mm]258Mounting methodSuspensionType of control gearLED - Betriebsgerät stromgesteuertLamp typeLED nicht austauschbarType of fasteningSeilabhängungImpact strengthIK08Degree of protection (IP)IP65Control gear includedyes	Width [mm]	258.0
Diameter [mm] 258 Mounting method Suspension Type of control gear LED - Betriebsgerät stromgesteuert Lamp type LED nicht austauschbar Type of fastening Seilabhängung Impact strength IK08 Degree of protection (IP) IP65 Control gear included yes	Length [mm]	258.0
Mounting method Type of control gear LED - Betriebsgerät stromgesteuert Lamp type LED nicht austauschbar Type of fastening Seilabhängung Impact strength Iko8 Degree of protection (IP) IP65 Control gear included Suspension LED - Betriebsgerät stromgesteuert LED nicht austauschbar Seilabhängung Iko8 Ivo8 Iv	Height/depth [mm]	139
Type of control gear Lamp type LED - Betriebsgerät stromgesteuert LED nicht austauschbar Type of fastening Seilabhängung Impact strength IK08 Degree of protection (IP) IP65 Control gear included LED - Betriebsgerät stromgesteuert LED nicht austauschbar IK08 IK08	Diameter [mm]	258
Lamp typeLED nicht austauschbarType of fasteningSeilabhängungImpact strengthIK08Degree of protection (IP)IP65Control gear includedyes	Mounting method	Suspension
Type of fastening Seilabhängung Impact strength IKO8 Degree of protection (IP) IP65 Control gear included yes	Type of control gear	LED - Betriebsgerät stromgesteuert
Impact strength IK08 Degree of protection (IP) IP65 Control gear included yes	Lamp type	LED nicht austauschbar
Degree of protection (IP) IP65 Control gear included yes	Type of fastening	Seilabhängung
Control gear included yes	Impact strength	IK08
	Degree of protection (IP)	IP65
Suspension included in delivery nein		
	Control gear included	yes

ELECTRICAL DATA

Protection class	I
Voltage type	AC
Nominal voltage [V]	100 - 277
Operating frequency [Hz]	50 - 60
Overall efficiency [lm/W]	150
Max. system power [W]	100
Power factor	0.95

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	symmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	15000
Colour temperature [K]	5000
Colour of light	White
Colour consistency (McAdam ellipse)	SDCM6

TEMPERATURE TECHNICAL DATA

Impact strength	IK08
Ambient temperature during operating [°C]	- 40 + 60
Rated life time L70/B10 at 25 °C [h]	50000

PACKAGING INFORMATION

BL High Bays Pure

BL HB Pure+ pendant luminaire 258mm 15000lm 100W 120D 850 230V

Article no.: 742091



EAN	4250716949544
Article no.	742091
Net weight [g]	1800
Gross weight [g]	2400
Gross width [mm]	305.0
Gross height [mm]	145.0
Gross length [mm]	305.0
Customs tariff number	94054099
Net width [mm]	258.0
Net height [mm]	139
Net length [mm]	258
State of origin	CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at