
# BL iTouch Platine

**BL iTouch circuit board for 24V light strips with touch function**
Article no.: 171735






## TENDER TEXT

BL Touch Sensor board for switching on, off and dimming by touch, Double-sided flexible circuit board, DC5~24V / 5A Input voltage = output voltage, 5% ~ 100% brightness dimmable, suitable for flexible LED strips

## TOP-FEATURES

//__ Im Profil integrierbar

//__ Bis 70 Watt einsetzbar

//__ Blaue Positions-LED

//__ Dimmung mittels Berührung

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261105 | Errors and printing errors are reserved.

# BL iTouch Platine

**BL iTouch circuit board for 24V light strips with touch function**
Article no.: 171735

## MECHANICAL DATA

| | |
|---|---|
| Material | sonstige |
| Width [mm] | 8.0 |
| Length [mm] | 40.0 |
| Height [mm] | 12.5 |
| Type of accessory | sonstige |
| Accessory | Yes |

## PACKAGING INFORMATION

| | |
|---|---|
| Article no. | 171735 |
| Net weight [g] | 0.6 |
| Gross weight [g] | 7.8 |
| Gross width [mm] | 60.0 |
| Gross height [mm] | 60.0 |
| Gross length [mm] | 40.0 |
| Customs tariff number | 8536500090 |
| Net width [mm] | 8.0 |
| Net height [mm] | 12.5 |
| Net length [mm] | 40 |
| State of origin | CN |

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 10% (or -/+ 15 %at ECO / TWO / RGB / AIR ). Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261105 | Errors and printing errors are reserved.