
BL Moisture-proof luminaire Pure+

BL MPR Pure+ moisture-proof luminaire 1221mm 5600lm 40W 120D 840 230V

Article no.: 752021









IP65

Degree of protection (IP)





TENDER TEXT

LED damp-proof light, plastic housing with aluminum interior, IP65, IK08, 4000K, luminous flux 5,600 lm, 140 lm/W, CRI>80, incl. converter, fire-protected, through-wiring possible, 1,221x74x64mm, BL Moisture-proof luminaire Pure+ Article 752021 LED moisture-proof luminaire made of Kunststoff , switchable luminaire with LED converter - yes mounted in housing, mounting type Anbau - ceiling mounting with enclosed Mounting brackets possible, geeignet für Durchgangsverdrahtung , switch nein , fireproof yes , protection classIP65 , impact resistance IK08 , Lifetime of 50000 h , Power 40 W, Colour rendering >80 , colour temperature 4000 K, beam angle 120°, ambient temperature -20...+40 °C, dimensions (L/W/H): 1221.0 mm x 74.0 mm x 64 mm

TOP-FEATURES

//__ Very robust thanks to protection class IP65

//_ Fireproof yes

//__ Impact resistance IK08



BL Moisture-proof luminaire Pure+

BL MPR Pure+ moisture-proof luminaire 1221mm 5600lm 40W 120D 840 230V

Article no.: 752021



MECHANICAL DATA

| Material | Kunststoff |
|---------------------------|------------------------|
| Colour housing | White |
| Width [mm] | 74.0 |
| Length [mm] | 1221.0 |
| Height/depth [mm] | 64 |
| Mounting method | Anbau |
| With movement sensor | nein |
| With switch | nein |
| Lamp type | LED nicht austauschbar |
| Type of fastening | Mounting brackets |
| Material of the cover | Plastic opal |
| Impact strength | IK08 |
| Degree of protection (IP) | IP65 |
| With lamp | yes |
| Control gear included | yes |
| Fireproof | yes |

ELECTRICAL DATA

| Nominal voltage [V] | 220 - 240 |
|---------------------------|------------------------------------|
| Operating frequency [Hz] | 50 / 60 |
| Overall efficiency [lm/W] | 140 |
| Max. system power [W] | 40 |
| Power factor | 0.95 |
| Type of wiring | geeignet für Durchgangsverdrahtung |

LIGHT TECHNICAL DATA

| Colour rendering index CRI >80 Light exit direkt Light distribution symmetrical |
|---|
| |
| Light distribution symmetrical |
| |
| Rated luminous flux according to IEC 62722-2-1 [lm] 5600 |
| Colour temperature [K] 4000 |
| Colour of light White |
| Colour consistency (McAdam ellipse) SDCM6 |

TEMPERATURE TECHNICAL DATA

| Impact strength | IK08 |
|---|-----------|
| Ambient temperature during operating [°C] | - 20 + 40 |
| Rated life time L70/B10 at 25 °C [h] | 50000 |

BL Moisture-proof luminaire Pure+

BL MPR Pure+ moisture-proof luminaire 1221mm 5600lm 40W 120D 840 230V

Article no.: 752021



PACKAGING INFORMATION

| EAN | 4250716949452 |
|-----------------------|---------------|
| Article no. | 752021 |
| Net weight [g] | 9000 |
| Gross weight [g] | 10500 |
| Gross width [mm] | 80.0 |
| Gross height [mm] | 70.0 |
| Gross length [mm] | 1280.0 |
| Customs tariff number | 94054099 |
| Net width [mm] | 74.0 |
| Net height [mm] | 64 |
| Net length [mm] | 1221 |
| State of origin | CN |

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at