


# BL Moisture-proof luminaire Trend


BL MPR Trend moisture-proof luminaire 1500mm 7500lm 26-50W 120D 840 white 230V  
Article no.: 751019



Impact strength



Degree of protection (IP)



Fireproof



Type of wiring

## TENDER TEXT

LED MPR damp-proof luminaire, 7,500 lumens, 50W, 120° direct beam, CRI >80, 4,000 Kelvin, IP65, IK08, protection class I, non-dimmable, fireproof, UV-resistant, white PC housing, incl. power supply unit, switching capacity: 26, 34, 42, 50W, dimensions: L 1500mm x W 59mm x H 60mm BL Moisture-proof luminaire Trend Article 751019 LED damp room light made of PC (Polycarbonat), switchable light with LED converter - Yes - mounted in housing, mounting type Anbau - ceiling mounting with enclosed Mounting brackets possible, quick assembly with, suitable for geeignet für Durchgangsverdrahtung, UV-resistant, fireproof Yes, protection class IP65, shock resistance IK08, corrosion protection, explosion protection, explosion protection Yes, service life of 50000 h, Power 50 W, Color Rendering >80, Color Temperature 4000 K, Beam Angle 120°, Ambient Temperature, Dimensions (L/W/H): 1500.0 mm x 59.0 mm x 60 mm

## TOP-FEATURES

//\_\_ Output or luminous flux can be adjusted directly via a DIP switch

//\_\_ Suitable for applications with high safety requirements - ideal for damp environments, industrial settings, car parks and outdoor areas

//\_\_ Low-maintenance and reliable even under difficult conditions



# BL Moisture-proof luminaire Trend

BL MPR Trend moisture-proof luminaire 1500mm 7500lm 26-50W 120D 840 white 230V

Article no.: 751019



## MECHANICAL DATA

Material	PC (Polycarbonat)
Colour housing	White
Width [mm]	59.0
Length [mm]	1500.0
Height/depth [mm]	60
Mounting method	Anbau
Type of control gear	LED - Betriebsgerät stromgesteuert
Lamp type	LED nicht austauschbar
Type of fastening	Mounting brackets
Suitable for emergency lighting	nein
Material of the cover	Plastic Opal
Impact strength	IK08
Degree of protection (IP)	IP65
With lamp	Yes
Control gear included	Yes
Fireproof	Yes

## ELECTRICAL DATA

Protection class	I
Voltage type	AC
Nominal voltage [V]	200 - 240
Operating frequency [Hz]	50 / 60
Overall efficiency [lm/W]	150
Max. system power [W]	50
Power factor	0.95
Type of wiring	geeignet für Durchgangsverdrahtung
No dim function	Yes

## LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Light exit	direkt
Light distribution	Symmetrical
Rated luminous flux according to IEC 62722-2-1 [lm]	7500
Colour temperature [K]	4000
Colour of light	White
Energy efficiency class of the built-in lamp	D

## TEMPERATURE TECHNICAL DATA

Impact strength	IK08
-----------------	------

# BL Moisture-proof luminaire Trend

**BL MPR Trend moisture-proof luminaire 1500mm 7500lm 26-50W 120D 840 white 230V**

Article no.: 751019



Rated life time L70/B50 at 25 °C [h] 50000

---

## PACKAGING INFORMATION

EAN 4250716953442

---

Article no. 751019

---

Net weight [g] 1010

---

Gross weight [g] 1210

---

Gross width [mm] 61.5

---

Gross height [mm] 61.5

---

Gross length [mm] 1540.0

---

Net width [mm] 59.0

---

Net height [mm] 60

---

Net length [mm] 1500

---

State of origin CN

---

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)