

BL ONE Comfort 1000 >80

BL ONE Comfort LED strip 980lm/m 24VDC 7.1W/m IP20 830 20m

Article no.: 100144



Lamp voltage



Max. length



Colour rendering index CRI



Luminous flux per meter

TENDER TEXT

LED strip ONE Comfort 980 lm/m 24VDC 7.1W/m 138lm/W IP20 CRI>80 3000K, without connection cable, WHITE 20 meter LED module BL ONE Comfort 1000 >80 Article 100144 Linear LED light strip IC-controlled on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 72000 h. The BL ONE Comfort 1000 >80 LED-strip has a luminous flux of 980 lm at 7.1 W, resulting in an efficiency of 138 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 9000 mm can be achieved. In terms of lighting, the module has a colour temperature of 3000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP20. Dimension (L x W x H): 20000.0 mm x 8.0 mm x 1.5 mm

TOP-FEATURES

- //_ Wide range of lumens and light colours
- //_ Maximum homogeneity thanks to 140 LEDs per metre
- //_ Economical energy consumption
- //_ Produced in Austria



BL ONE Comfort 1000 >80

BL ONE Comfort LED strip 980lm/m 24VDC 7.1W/m IP20 830 20m

Article no.: 100144



MECHANICAL DATA

Width [mm]	8.0
Length [mm]	20000.0
Height/depth [mm]	1.5
Colour	White
Model	Band
Self-adhesive	Yes
Lamp type	LED nicht austauschbar
Distance [mm]	7.14
Distance relating to	LED zu LED
Degree of protection (IP)	IP20
Length of particular segments [mm]	50.0
Lowest bending radius [mm]	20
Number of lamps per meter	140

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Input voltage range [V]	23 - 25
Lamp power per meter [W]	7.1
Overall efficiency [lm/W]	138

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Colour temperature [K]	3000
Colour of light	neutral white
Luminous flux per meter [lm]	980
Energy efficiency class provided exchangeable built-in lamp	E
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section [mm ²]	0.5
Number of poles	2
Max. length [mm]	9000

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	0 ... + 60
Operation temperature at T _c [°C]	- 5 ... + 60
Ambient temperature during operating [°C]	- 20 ... + 45

BL ONE Comfort 1000 >80

BL ONE Comfort LED strip 980lm/m 24VDC 7.1W/m IP20 830 20m

Article no.: 100144



Rated life time L80/B10 at 25 °C [h] 72000

PACKAGING INFORMATION

EAN 4250716947939

Article no. 100144

Customs tariff number 9405423990

Net width [mm] 8.0

Net height [mm] 1.5

Net length [mm] 20000

State of origin AT

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 °C ambient temperature under the standardized measuring environment of BILTON LEDON Technology. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at