

BL ONE Select Retail 2000

BL ONE Select Retail LED strip 2000lm/m 24VDC 17.9W/m IP20 940 5m

Article no.: 101830







TENDER TEXT

LED strip ONE Select Retail 2000 lm/m 24VDC, 17.9W/m, 112 lm/W, IP20, CRI>95, 4000K, WHITE, connection cable 500 mm on both sides, 5 metres LED module BL ONE Select Retail 2000 Article 101830 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BL ONE Select Retail 2000 LED-strip has a luminous flux of 2000 lm at 17.9 W, resulting in an efficiency of 112 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 5500 mm can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 120°. All this with a colour rendering index of >95 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

TOP-FEATURES

- // Best light quality for shop lighting thanks to CRI >95
- $//_$ Long line lengths and better stability due to double layer
- //_ Wide choice of light colors and lumen packages
- $//_$ Available in Degree of Protection IP20



BL ONE Select Retail 2000

BL ONE Select Retail LED strip 2000lm/m 24VDC 17.9W/m IP20 940 5m

Article no.: 101830



MECHANICAL DATA

8.0
5000.0
1.5
1.5
White
Band
yes
LED nicht austauschbar
7.14
LED zu LED
IP20
50.0
20
yes
nein
140

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Lamp power per meter [W]	17.9
Overall efficiency [lm/W]	112

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>95
Colour temperature [K]	4000
Colour of light	White
Luminous flux per meter [lm]	2000
Energy efficiency class provided exchangeable built-in lamp	F
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	2
Max. length [mm]	5500

TEMPERATURE TECHNICAL DATA

BL ONE Select Retail 2000

BL ONE Select Retail LED strip 2000lm/m 24VDC 17.9W/m IP20 940 5m

Article no.: 101830



Ambient/storage temperature [°C]	- 5 + 55
Operation temperature at Tc [°C]	- 5 + 60
Ambient temperature during operating [°C]	- 20 + 45
Rated life time L80/B10 at 25 °C [h]	60000

PACKAGING INFORMATION

EAN	4250716935851
Article no.	101830
Gross width [mm]	200.0
Gross height [mm]	18.0
Gross length [mm]	200.0
Customs tariff number	94054099
Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	5000
State of origin	AT

^{*} Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at