
BL ONE Select XL 3000 >80

BL ONE Select XL LED strip 2770lm/m 24VDC 21.3W/m IP20 827 20m

Article no.: 101783










Lamp voltage



Max. length



Colour rendering index CRI Luminous flux per meter



TENDER TEXT

LED strip ONE Select XL 2770 lm/m 24VDC, 21.3 W/m, 130 lm/W, IP20, CRI>80, 2700K, WHITE, module width 12 mm, connection cable 500 mm on both sides, 20 metres LED module BL ONE Select XL 3000 >80 Article 101783 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BL ONE Select XL 3000 >80 LED-strip has a luminous flux of 2770 lm at 21.3 W, resulting in an efficiency of 130 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 6000 mm can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP20 Dimension (L x W x H): 20000.0 mm x 12.0 mm x 1.5 mm

TOP-FEATURES

// High lumen packages up to 2770 lm

//__ Module width of 12.0 mm for thermal conduction and long line lengths

//__ High design freedom, current capacity and longer module lengths are achievable















BL ONE Select XL 3000 >80

BL ONE Select XL LED strip 2770lm/m 24VDC 21.3W/m IP20 827 20m

Article no.: 101783



MECHANICAL DATA

Length [mm] 20000.0 Height/depth [mm] 1.5 Height [mm] 1.5 Colour White Model Band	
Height [mm] 1.5 Colour White	
Colour White	
Model Rand	
Pilotei Bullu	
Self-adhesive yes	
Lamp type LED nicht austauschbar	
Distance [mm] 7.14	
Distance relating to LED zu LED	
Degree of protection (IP) IP20	
Length of particular segments [mm] 50.0	
Lowest bending radius [mm] 20	
With connection set yes	
With end piece nein	
Number of lamps per meter 140	

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Lamp power per meter [W]	21.3
Overall efficiency [lm/W]	130

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>80
Colour temperature [K]	2700
Colour of light	White
Luminous flux per meter [lm]	2770
Energy efficiency class provided exchangeable built-in lamp	E
Colour consistency (McAdam ellipse)	SDCM3

CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	2
Max. length [mm]	6000

TEMPERATURE TECHNICAL DATA

BL ONE Select XL 3000 >80

BL ONE Select XL LED strip 2770lm/m 24VDC 21.3W/m IP20 827 20m

Article no.: 101783



Ambient/storage temperature [°C]	- 5 + 55
Operation temperature at Tc [°C]	- 5 + 60
Ambient temperature during operating [°C]	- 20 + 45
Rated life time L80/B10 at 25 °C [h]	60000

PACKAGING INFORMATION

EAN	4250716935387
Article no.	101783
Gross width [mm]	200.0
Gross height [mm]	22.0
Gross length [mm]	200.0
Customs tariff number	94054099
Net width [mm]	12.0
Net height [mm]	1.5
Net length [mm]	20000
State of origin	AT

^{*} Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at