
# BL ONE Select XL 5000 >90

#### BL ONE Select XL LED strip 5050lm/m 24VDC 41.5W/m IP20 965 20m

Article no.: 101928









Lamp voltage



Max. length



Colour rendering index CRI Luminous flux per meter



#### **TENDER TEXT**

LED strip ONE Select XL 5050 lm/m 24VDC, 41.5W/m, 122 lm/W, IP20, CRI>90, 6500K, WHITE, module width 12 mm, connection cable 500 mm on both sides, 20 metres LED module BL ONE Select XL 5000 > 90 Article 101928 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BL ONE Select XL 5000 >90 LED-strip has a luminous flux of 5050 lm at 41.5 W, resulting in an efficiency of 122 lm/W. At a nominal voltage of 24  $\,$ V DC on the connection, a maximum module length of 3500 mm can be achieved. In terms of lighting, the module has a colour temperature of 6500 K and a beam angle of 120°. All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP20 Dimension (L x W x H): 20000.0 mm x 12.0 mm x 1.5 mm

#### **TOP-FEATURES**

// Best light quality for shop lighting with CRI >90

//\_ High lumen packages up to 5050 lm

//\_\_ Module width of 12.0 mm for thermal conduction and long line lengths

//\_ High design freedom, current capacity and longer module lengths are achievable

















# BL ONE Select XL 5000 >90

### BL ONE Select XL LED strip 5050lm/m 24VDC 41.5W/m IP20 965 20m

Article no.: 101928



### MECHANICAL DATA

Width [mm]	2.0
Length [mm] 2	0000.0
Height/depth [mm]	.5
Height [mm]	.5
Colour	Vhite
Model B	land
Self-adhesive ye	es
Lamp type	ED nicht austauschbar
Distance [mm] 7.	.14
Distance relating to	ED zu LED
Degree of protection (IP)	220
Length of particular segments [mm] 56	0.0
Lowest bending radius [mm] 2	0
With connection set ye	es
With end piece ne	ein
Number of lamps per meter 1-	40

# **ELECTRICAL DATA**

Protection class	III
Voltage type	DC
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Lamp power per meter [W]	41.5
Overall efficiency [lm/W]	122

# LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour rendering index CRI	>90
Colour temperature [K]	6500
Colour of light	White
Luminous flux per meter [lm]	5050
Energy efficiency class provided exchangeable built-in lamp	E
Colour consistency (McAdam ellipse)	SDCM3

# CONNECTION

Conductor cross section [mm²]	0.5
Number of poles	2
Max. length [mm]	3500

# TEMPERATURE TECHNICAL DATA

# BL ONE Select XL 5000 >90

#### BL ONE Select XL LED strip 5050lm/m 24VDC 41.5W/m IP20 965 20m

Article no.: 101928



Rated life time L80/B10 at 25 °C [h]	60000
Ambient temperature during operating [°C]	- 20 + 45
Operation temperature at Tc [°C]	- 5 + 60
Ambient/storage temperature [°C]	- 5 + 55

### PACKAGING INFORMATION

EAN	4250716938159
Article no.	101928
Gross width [mm]	200.0
Gross height [mm]	22.0
Gross length [mm]	200.0
Customs tariff number	94054099
Net width [mm]	12.0
Net height [mm]	1.5
Net length [mm]	20000
State of origin	AT

<sup>\*</sup> Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at