


BL Panel Comfort

BL Panel Comfort 620mm 3800lm 30W 90D 930 white 900mA

Article no.: 710112



Colour housing



Degree of protection (IP)



Colour of light

TENDER TEXT

LED panel, 3,800 lumen, 30W, 90° direct beam, CRI >90, 3,000 Kelvin, IP20, protection class III, dimmable, UGR BL Panel Comfort Article 710112 LED panel for installation as Surface / Installation / Suspension - made of high-quality, White coated frames made of Aluminium . Microprismatic layer for modular ceilings with concealed or visible support system. Very flat and compact design with a total height of 10 mm. Best light quality with precise glare control 90 ; light color White , color temperature 3000 K; beam angle 90°, mounting set for Surface / Installation / Suspension must be ordered separately. Dimensions (L x W x H): 620.0 mm x 620.0 mm x 10 mm

TOP-FEATURES

//__ LED panel light with microprismatic layer for modular ceilings with concealed or visible support system

//__ Best light quality with precise glare control and homogeneous light distribution over the entire light emission surface

//__ Glare limitation (UGR) <19



BL Panel Comfort

BL Panel Comfort 620mm 3800lm 30W 90D 930 white 900mA

Article no.: 710112



MECHANICAL DATA

Material housing	Aluminium
Colour housing	White
Width [mm]	620.0
Length [mm]	620.0
Height/depth [mm]	10
Mounting method	Surface / Installation / Suspension
With movement sensor	nein
Lamp type	LED nicht austauschbar
Material of the cover	Plastic structured
Degree of protection (IP)	IP20
Control gear included	nein
Unified Glare Ratio (UGR)	<19

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Nominal voltage [V]	29,9 - 36,6
Overall efficiency [lm/W]	127
Nennstrom [A]	0,9
Max. system power [W]	30

LIGHT TECHNICAL DATA

Beam angle [°]	90
Colour rendering index CRI	>90
Light exit	direkt
Rated luminous flux according to IEC 62722-2-1 [lm]	3800
Colour temperature [K]	3000
Colour of light	White
Energy efficiency class of the built-in lamp	E
Colour consistency (McAdam ellipse)	SDCM4

TEMPERATURE TECHNICAL DATA

Rated life time L80/B50 at 25 °C [h]	50000
--------------------------------------	-------

PACKAGING INFORMATION

EAN	4250716949063
Article no.	710112
Net weight [g]	2480
Gross weight [g]	5000
Gross width [mm]	655.0

BL Panel Comfort

BL Panel Comfort 620mm 3800lm 30W 90D 930 white 900mA

Article no.: 710112



Gross height [mm]	62.0
Gross length [mm]	665.0
Customs tariff number	94054239
Net width [mm]	620.0
Net height [mm]	10
Net length [mm]	620
State of origin	CN

NECESSARY ACCESSORIES

Article	Article no.
---------	-------------

LED DRIVER 220-240V CC 900mA 9-45VDC DALI 719241	
---	--

LED DRIVER 220-240V CC 900mA 27-42VDC	719246
ON/OFF	

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at