
BL Panel Comfort

BL Panel Comfort 623mm 4000lm 30W 90D 940 white 900mA

Article no.: 710115













TENDER TEXT

LED panel, 4,000 lumen, 30W, 90° direct beam, CRI >90, 4,000 Kelvin, IP20, protection class III, dimmable, UGR BL Panel Comfort Article 710115 LED panel for installation as Surface / Installation / Suspension - made of high-quality, White coated frames made of Aluminium . Microprismatic layer for modular ceilings with concealed or visible support system. Very flat and compact design with a total height of 10 mm. Best light quality with precise glare control 90 ; light color White , color temperature 4000 K; beam angle 90°, mounting set for Surface / Installation / Suspension must be ordered separately. Dimensions (L x W x H): 623.0 mm x 623.0 mm x 10 mm

TOP-FEATURES

//_ LED panel light with microprismatic layer for modular ceilings with concealed or visible support system

//_ Best light quality with precise glare control and homogeneous light distribution over the entire light emission surface

//__ Glare limitation (UGR) <19











BL Panel Comfort

BL Panel Comfort 623mm 4000lm 30W 90D 940 white 900mA

Article no.: 710115



MECHANICAL DATA

Colour housingWhiteWidth [mm]623.0Length [mm]623.0Height/depth [mm]10Mounting methodSurface / Installation / SuspensionWith movement sensorneinLamp typeLED nicht austauschbarMaterial of the coverPlastic structuredDegree of protection (IP)IP20Control gear includednein	Material housing	Aluminium
Length [mm] 623.0 Height/depth [mm] 10 Mounting method Surface / Installation / Suspension With movement sensor nein Lamp type LED nicht austauschbar Material of the cover Plastic structured Degree of protection (IP) IP20	Colour housing	White
Height/depth [mm] 10 Mounting method Surface / Installation / Suspension With movement sensor nein Lamp type LED nicht austauschbar Material of the cover Plastic structured Degree of protection (IP) IP20	Width [mm]	623.0
Mounting method Surface / Installation / Suspension With movement sensor nein Lamp type LED nicht austauschbar Material of the cover Plastic structured Degree of protection (IP) IP20	Length [mm]	623.0
With movement sensor nein Lamp type LED nicht austauschbar Material of the cover Plastic structured Degree of protection (IP) IP20	Height/depth [mm]	10
Lamp type LED nicht austauschbar Material of the cover Plastic structured Degree of protection (IP) IP20	Mounting method	Surface / Installation / Suspension
Material of the cover Plastic structured Degree of protection (IP) IP20	With movement sensor	nein
Degree of protection (IP) IP20	Lamp type	LED nicht austauschbar
	Matarial of the server	
Control gear included nein	Material of the cover	Plastic structured
Unified Glare Ratio (UGR) <19	Degree of protection (IP)	IP20

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Nominal voltage [V]	29,9 - 36,6
Overall efficiency [lm/W]	133
Nennstrom [A]	0,9
Max. system power [W]	30

LIGHT TECHNICAL DATA

Beam angle [°]	90
Colour rendering index CRI	>90
Light exit	direkt
Rated luminous flux according to IEC 62722-2-1 [lm]	4000
Colour temperature [K]	4000
Colour of light	White
Energy efficiency class of teh built-in lamp	D
Colour consistency (McAdam ellipse)	SDCM4

TEMPERATURE TECHNICAL DATA

Rated life time L80/B50 at 25 $^{\circ}$ C [h] 50000

PACKAGING INFORMATION

EAN	4250716949094
Article no.	710115
Net weight [g]	2560
Gross weight [g]	5200
Gross width [mm]	655.0

BL Panel Comfort

BL Panel Comfort 623mm 4000lm 30W 90D 940 white 900mA

Article no.: 710115



Gross height [mm]	62.0
Gross length [mm]	665.0
Customs tariff number	94054239
Net width [mm]	623.0
Net height [mm]	10
Net length [mm]	623
State of origin	CN

NECESSARY ACCESSORIES

Article no.

LED DRIVER 220-240V CC 900mA 9-45VDC DALI 719241 LED DRIVER 220-240V CC 900mA 27-42VDC 719246 ON/OFF

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at