

Power Supply DALI Downlight

BL TCI Power supply CC 220-240VAC 10-49VDC 350mA IP20 DALI

Article no.: 729026



BILTON LEDON
BETTER LIGHT

Oops – erwischt!

Hier folgt bald das gewünschte Bild.

TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 10-49VDC. Output current 350mA. DALI control signal. Protection class IP20. Protection class II. Dimensions LxWxH = 108x52x22mm



Power Supply DALI Downlight

BL TCI Power supply CC 220-240VAC 10-49VDC 350mA IP20 DALI

Article no.: 729026



MECHANICAL DATA

Width [mm]	52.0
Length [mm]	108.0
Height [mm]	22.0
Control signal	DALI
Degree of protection (IP)	IP20
Core cross section [mm ²]	0,5 - 1,5

ELECTRICAL DATA

Protection class	III
Voltage type	AC
Control signal	DALI
Input voltage range [V]	220 - 240
Output power range [W]	12,5
Frequency supply voltage (range) [Hz]	50 - 60
Output current range [mA]	72
Dimming DALI	yes

CONNECTION

Core cross section [mm ²]	0,5 - 1,5
---------------------------------------	-----------

TEMPERATURE TECHNICAL DATA

Lifespan at 20 °C [h]	50000
-----------------------	-------

PACKAGING INFORMATION

EAN	9009453013187
Article no.	729026
Net weight [g]	106
Gross weight [g]	106
State of origin	IT

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at