Schaltbar

BL TRI Power supply unit CC 220-240VAC 25-43VDC 350mA IP20 on/off

Article no.: 729027



TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 25-43VDC. Output current 350mA. Protection class IP20. Protection class II. Dimensions LxWxH = 100x43x22.5mm



Schaltbar

BL TRI Power supply unit CC 220-240VAC 25-43VDC 350mA IP20 on/off

Article no.: 729027



MECHANICAL DATA

| Width [mm] | 43.0 |
|---------------------------|-----------|
| Length [mm] | 100.0 |
| Height [mm] | 22.5 |
| Control signal | ohne |
| Degree of protection (IP) | IP20 |
| Core cross section [mm²] | 0,5 - 1,5 |

ELECTRICAL DATA

| Protection class | III |
|---------------------------------------|-----------|
| Voltage type | AC |
| Lamp voltage [V] | 230 |
| Control signal | ohne |
| Imput voltage range [V] | 220 - 240 |
| Output power range [W] | 12,5 |
| Frequency supply voltage (range) [Hz] | 50 - 60 |

LIGHT TECHNICAL DATA

Colour temperature [K]

CONNECTION

Core cross section [mm²] 0,5 - 1,5

PACKAGING INFORMATION

| EAN | 9009453012807 |
|------------------|---------------|
| Article no. | 729027 |
| Net weight [g] | 58 |
| Gross weight [g] | 58 |
| State of origin | CN |

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at