



Abdeckung BLine C-S black

BLine C-S-01 black cover, flat, rollable, 20,000 mm, for P-S-IN/ON/COR 01

Article no.: 171985



Bore/transmittance



Net height

TENDER TEXT

Cover black PC, 21% rollable, 20m for P-S-IN/ON/COR profiles 01

TOP-FEATURES

- //_ Covers available in black, satined and transparent
- //_ Black and satined cover available to 20 metres/roll



Abdeckung BLine C-S black

BLine C-S-01 black cover, flat, rollable, 20,000 mm, for P-S-IN/ON/COR 01

Article no.: 171985



MECHANICAL DATA

Material	Kunststoff
Width [mm]	15.5
Length [mm]	20000.0
Mounting method	Aufbau / Einbau
Colour	Black
Model	Lengthwise cover
Suitable for	Einbau, Aufbau, Eck
Inflammability class of insulation material acc. with UL94	V2
Bore/transmittance [%]	21

TEMPERATURE TECHNICAL DATA

Inflammability class of insulation material acc. with UL94	V2
Bore/transmittance [%]	21

PACKAGING INFORMATION

EAN	4250716950854
Article no.	171985
Net weight [g]	460
Gross weight [g]	460
Customs tariff number	94054231
Net width [mm]	15.5
Net height [mm]	4.4
Net length [mm]	20000
State of origin	CN

* Our aluminum profiles, plastic profiles, and associated accessories are intended exclusively for use in LED lighting, especially LED strips. They serve as integral components of luminaires and are designed for this purpose. Any other use, especially any misuse outside of LED lighting, is beyond our responsibility.

We assume no liability for damages or consequential costs resulting from improper use of our products.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at