
Endcap BLine Select CT00

BLine Select CT00 end cap white for profile CT02 and lens CX05 without hole
Article no.: 170436





4.0 mm	12.5 mm	grau	6 mm
Length	Covering width	Colour	Net height

TENDER TEXT

End cap for CT02 + cover flat, POM installation dim. 1.5 mm without hole, W 12.5 x H 6 x L4 mm BILTON LEDON Technology Endcap BLine Select CT00 Article 170436 The Endcap BLine Select CT00 consists of Kunststoff and has a grau . Easy installation via into the profile. Dimension (L x W x H): 4.0 mm x 12.5 mm x 6 mm

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261115 | Errors and printing errors are reserved.

Endcap BLine Select CT00

BLine Select CT00 end cap white for profile CT02 and lens CX05 without hole
Article no.: 170436

MECHANICAL DATA

Material	Kunststoff
Width [mm]	12.5
Length [mm]	4.0
Covering width [mm]	12.5
Colour	grau
Model	Endkappe
Suitable for	U - Profil
Surfacetreatment	unbehandelt

TEMPERATURE TECHNICAL DATA

Thermal conductivity	100

PACKAGING INFORMATION

EAN	4250716910575
Article no.	170436
Net weight [g]	0.1
Gross weight [g]	3
Gross width [mm]	50.0
Gross length [mm]	100.0
Customs tariff number	39169050
Net width [mm]	12.5
Net height [mm]	6
Net length [mm]	4
State of origin	DE

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261115 | Errors and printing errors are reserved.