Spring steel BLine Select XTC2

BLine Select XTC2 installation spring steel for alu profiles W21.5xH15xL40mm
Article no.: 170455





40.0 mm	15.0 mm	21.5 mm
Length	Height	Width

TENDER TEXT

Mounting material for aluminium profiles, Installation spring made of steel, W 21.5 x H 15 x L40 mm Accessories Spring steel BLine Select XTC2 Article 170455 The accessories Spring steel BLine Select XTC2 consists of Edelstahl with a Edelstahl surface and it is easy to assemble. Dimension (L x W x H): 40.0 mm x 21.5 mm x 15.0 mm

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261127 | Errors and printing errors are reserved.

Spring steel BLine Select XTC2

BLine Select XTC2 installation spring steel for alu profiles W21.5xH15xL40mm
Article no.: 170455

MECHANICAL DATA

Material	Edelstahl
Width [mm]	21.5
Length [mm]	40.0
Height [mm]	15.0
Colour	Edelstahl
Type of accessory	Einbaugehäuse
Transparent	nein
Accessory	Yes

TEMPERATURE TECHNICAL DATA

Thermal conductivity	16.5

PACKAGING INFORMATION

EAN	4250716905762
Article no.	170455
Net weight [g]	9
Gross weight [g]	12
Gross width [mm]	90.0
Gross height [mm]	5.0
Gross length [mm]	120.0
Customs tariff number	76042990
Net width [mm]	21.5
Net height [mm]	15
Net length [mm]	40
State of origin	DE

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261127 | Errors and printing errors are reserved.