

# Panel Comfort TW

LED DRIVER 220-240V CC 2x850mA 20-42VDC DT8 SW

Article no.: 719224



DALI

Control signal

IP20

Degree of protection (IP)

850

mA

Output current range

Yes

Dimming DALI

## TENDER TEXT

LED converter Adaptive White, switch DIM, DT 8, dimensions: 215x70x31mm BILTON LEDON Technology Panel Comfort TW Article 719224 The power supply can be used for a output voltage range of . Constant current 850 mA. The supply voltage of the power supply is 220 - 240 V and has a IP20 protection type and protection class III . Control signal DALI . Dimensions (L x W x H): 215.0 mm x 70.0 mm x 31.0 mm



# Panel Comfort TW

LED DRIVER 220-240V CC 2x850mA 20-42VDC DT8 SW

Article no.: 719224



## MECHANICAL DATA

Width [mm]	70.0
Length [mm]	215.0
Height [mm]	31.0
Model	dynamisch
Control signal	DALI
Suitable for outdoor use	nein
Degree of protection (IP)	IP20

## ELECTRICAL DATA

Protection class	III
Voltage type	AC
Control signal	DALI
Input voltage range [V]	220 - 240
Output current range [mA]	850
Suitable for constant current	Yes
Suitable for constant voltage	nein
Dimming DALI	Yes

## PACKAGING INFORMATION

EAN	4250716949780
Article no.	719224
Net weight [g]	238
Gross weight [g]	238
Net width [mm]	70.0
Net height [mm]	31
Net length [mm]	215
State of origin	AT

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)