

# Downlight Protected

LED DRIVER 220-240V CC 450mA 9-45VDC DALI Protected DL

Article no.: 729163



---

## TENDER TEXT

for DL Protected 145mm

---



# Downlight Protected

## LED DRIVER 220-240V CC 450mA 9-45VDC DALI Protected DL

Article no.: 729163



### MECHANICAL DATA

Housing	Kunststoffgehäuse
Width [mm]	44.0
Length [mm]	137.5
Height [mm]	23.0
Model	dynamisch
Control signal	DALI / Switch
With overheating protection	nein
Suitable for outdoor use	nein
Degree of protection (IP)	IP20
Core cross section [mm²]	0,5 - 1,5

### ELECTRICAL DATA

Protection class	II
Control signal	DALI / Switch
With overheating protection	nein
Input voltage range [V]	198 - 264
Output voltage range [V]	9 - 45
Output current range [mA]	450
Overload protection	yes
Standby power consumption (solstandby) [W]	0.45
Suitable for constant current	yes
Suitable for constant voltage	nein
Suitable for DC-voltage (primary side)	yes
Dimming DALI	yes

### CONNECTION

Core cross section [mm²]	0,5 - 1,5
--------------------------	-----------

### TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	- 20 ... + 80
Ambient temperature during operating [°C]	- 20 ... + 45

### PACKAGING INFORMATION

EAN	4250716950892
Article no.	729163
Customs tariff number	85044083
Net width [mm]	44.0
Net height [mm]	23
Net length [mm]	137.5
State of origin	CN

# Downlight Protected

**LED DRIVER 220-240V CC 450mA 9-45VDC DALI Protected DL**

Article no.: 729163



**SAFETY INFORMATION:** Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

**DISCLAIMER OF WARRANTY:** The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)