

# Power Supply switchable Downlight

LED DRIVER 220-240V CC 700MA 2-44VDC

Article no.: 729041



**BILTON LEDON**  
BETTER LIGHT

Oops – erwischt!

**Hier folgt bald das gewünschte Bild.**

---

## TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 5-44VDC. Output current 700mA. Protection class IP20. Protection class II. Dimensions LxWxH = 146.5x43.5x22mm



# Power Supply switchable Downlight

**LED DRIVER 220-240V CC 700MA 2-44VDC**

Article no.: 729041



## MECHANICAL DATA

Width [mm]	43.5
Length [mm]	146.5
Height [mm]	22.0
Control signal	ohne
Degree of protection (IP)	IP20

## ELECTRICAL DATA

Protection class	III
Voltage type	AC
Control signal	ohne
Input voltage range [V]	220 - 240
Standby power consumption (solstandby) [W]	18.5
No dim function	yes

## TEMPERATURE TECHNICAL DATA

Lifespan at 20 °C [h]	50000
-----------------------	-------

## PACKAGING INFORMATION

EAN	9009453012753
Article no.	729041
Net weight [g]	86
Gross weight [g]	86
Net width [mm]	43.5
Net height [mm]	22
Net length [mm]	146.5
State of origin	IT

**SAFETY INFORMATION:** Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

**DISCLAIMER OF WARRANTY:** The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)