Downlight Pure

LED DRIVER 220-240V CC 700mA 9-45VDC DALI

Article no.: 729175



DALI / Switc
Control signal

IP20
Degree of protection (IP)

700
mA
Output current range

Yes
Dimming DALI

TENDER TEXT

incl. connection cable for FDL240 BILTON LEDON Technology Downlight Pure Article 729175 The power supply can be used for a output voltage range of 9-45 V. Constant current 700 mA. The supply voltage of the power supply is 198 - 264 V and has a IP20 protection type and protection class II . Control signal DALI/Switch . Dimensions (L x W x H): 137.5 mm x 44.0 mm x 23.0 mm

IP20 | DALI / Switch | RoHS COMPLIANT 2022/95/EC | CE

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261031 | Errors and printing errors are reserved.

Downlight Pure

LED DRIVER 220-240V CC 700mA 9-45VDC DALI
Article no.: 729175

BETTER LIGHT

MECHANICAL DATA

Housing	Kunststoffgehäuse
Width [mm]	44.0
Length [mm]	137.5
Height [mm]	23.0
Model	dynamisch
Control signal	DALI / Switch
With overheating protection	nein
Suitable for outdoor use	nein
Degree of protection (IP)	IP20
Core cross section [mm²]	0,5 - 1,5

ELECTRICAL DATA

Protection class	II
Control signal	DALI / Switch
With overheating protection	nein
Imput voltage range [V]	198 - 264
Output voltage range [V]	9 - 45
Output current range [mA]	700
Overload protection	Yes
Standby power consumption (solstandby) [W]	0.45
Suitable for constant current	Yes
Suitable for constant voltage	nein
Suitable for DC-voltage (primary side)	Yes
Dimming DALI	Yes

CONNECTION

Core cross section [mm²]	0,5 - 1,5

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature [°C]	- 20 ... + 80
Ambient temperature during operating [°C]	- 20 ... + 45

PACKAGING INFORMATION

Article no.	729175
Customs tariff number	85044083
Net width [mm]	44.0
Net height [mm]	23
Net length [mm]	137.5
State of origin	CN

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261031 | Errors and printing errors are reserved.

Downlight Pure

LED DRIVER 220-240V CC 700mA 9-45VDC DALI

Article no.: 729175

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261031 | Errors and printing errors are reserved.